



Mobil™ Synthetic 5W-40 (MT80)

Mobil Passenger Vehicle Lube , 中国

Full Synthetic Engine Oil

Product Description

Mobil Synthetic 5W-40 (MT80) is a full synthetic engine oil which meets with API SP grade, designed to keep you worry free from various road condition.

Features and Benefits

- Meet with API SP grade
- allows easy and smooth starting during cold starts with good fluidity in low temperature
- it protects the engine in high temperature and keeps engine clean
- ability of controlling ashes, meet with China 6

Applications

Mobil Synthetic 5W-40 (MT80) is recommended for gasoline vehicles with 5W-40 viscosity grade recommended.

Specifications and Approvals

This product meets or exceeds the requirements of:
API SP

Properties and Specifications

Property	
Grade	SAE 5W-40
Viscosity Index, ASTM D2270	170
Total Base Number, mgKOH/g, ASTM D2896	8.5
Density @ 15.6 C, g/ml, ASTM D4052	0.858
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	14.1
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	86
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3.6
Pour Point, °C, ASTM D97	-42
Flash Point, Cleveland Open Cup, °C, ASTM D92	215
Ash, Sulfated, mass%, ASTM D874	0.8

Property	
Mini-Rotary Viscometer, Apparent Viscosity, -35 C, mPa.s, ASTM D4684	40100

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2022
ExxonMobil (China) Investment Co. Ltd
17th Floor, Metro Tower
30 Tian Yao Qiao Road
Shanghai 2000030
China

+86 21 24076000
<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil

Esso

MT80

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved