



Mobilgrease MP

Mobil Passenger Vehicle Lube , 中国

Lithium Automotive Grease

Product Description

Mobilgrease MP is a high quality, multipurpose, NLGI 2 grade, lithium hydroxystearate grease based on an ISO VG 150 mineral oil. It is formulated to provide added protection against rusting and washout in general purpose automotive applications at moderate temperatures and loads.

Features and Benefits

Mobilgrease MP has a long history of proven performance in general purpose automotive applications and provides the following benefits:

- Wide operating temperature range
- Good resistance to water washout
- Extra protection against rust and corrosion
- Good pumpability in centralized systems
- Excellent structural stability
- Lead, chlorine and nitrite free

Applications

Mobilgrease MP is recommended for the lubrication of automotive chassis components, wheel bearings, clutch bearings, universal joints and ball joints of steering and suspension systems on passenger cars, trucks, farm tractors and most other types of mobile equipment operating under moderate conditions. The recommended operating temperature range of Mobilgrease MP is -20°C to 120°C. In applications where heavy or shock loading is a factor, extreme pressure greases are preferred.

Typical Properties

Mobilgrease MP	Test Method	Unit	
CMCS Code			970422
NLGI Grade	ASTM D 217		2
Soap Type			Lithium
Color	Visual		Medium Brown
Structure	Visual		Smooth
Penetration, Worked	ASTM D 217		280
Dropping Point	ASTM D 2265	°C	180 (min)
Viscosity of Oil @ 40°C	ASTM D 445	cSt	150
Washout Test	IP 220 Mod		0-0

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via Internet. This product should not be used for purposes other than its intended use. If disposing of this product, take care to protect the environment.

The Mobil logotype, the Pegasus design and Mobilgrease MP are trademarks of ExxonMobil Corporation, or one of its subsidiaries.

09-2020

ExxonMobil (China) Investment Co. Ltd

17th Floor, Metro Tower

30 Tian Yao Qiao Road

Shanghai 2000030

China

+86 21 24076000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal use.

manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

The ExxonMobil logo, featuring the word "Exxon" in a bold, sans-serif font and "Mobil" in a similar font, with a stylized "X" connecting the two.The Exxon logo, which is a smaller version of the ExxonMobil logo.The Mobil logo, which is a smaller version of the ExxonMobil logo.

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved