



MOBIL ATF D/M MULTIPURPOSE

Mobil Passenger Vehicle Lube , 中国

Automatic Transmission Fluid

Product Description

Mobil ATF Multipurpose D/M is a premium synthetic technology transmission fluid formulated for use in a wide variety of 4 Speed and 5 Speed transmissions in North American, European, and Asian vehicles. It can also be used as power steering oil.

Features and Benefits

- High viscosity index – helps assure adequate lubrication and maintains viscosity stability at low start-up temperatures and high operating temperatures
- Corrosion prevention – helps provide protection against rusting and corrosion, plus special protection for soldered fittings
- Elastomer compatibility – is not harmful to synthetic rubber seal materials
- Good lubricating characteristics – gives quiet operation, smooth shifting and excellent wear protection
- Controlled friction properties – transmission of power is smooth and efficient throughout all normal temperature ranges

Applications

Mobil ATF Multipurpose D/M is a premium synthetic technology automatic transmission fluid designed to meet the needs of broad range of 4 speed and 5 speed transmission designs. Mobil ATF Multipurpose D/M is not recommended for use in 6 Speed plus step AT, CVT or DCT transmissions.

Good maintenance practice dictates that automatic transmissions be checked for proper fluid levels at regular intervals, and that the fluid be drained and replaced at intervals recommended by the manufacturer. Some manufacturers recommend more frequent changes of transmission fluid under severe driving conditions such as those that occur in heavy traffic, in hot weather, or when pulling a trailer.

Based on a combination of field-testing and laboratory testing, Mobil ATF Multipurpose D/M is suitable for use in applications requiring Dexron IIIH, Ford Mercon, etc.

Note: Mobil ATF Multipurpose D/M is not recommended for other application, including GM Dexron VI, Ford Mercon V, Mercon LV, Mercon SP and Type F ATF.

Mobil ATF Multipurpose D/M is suitable for use in a broad range of transmissions. It is important to note that the respective vehicle manufacturers have neither evaluated nor approved Multi-vehicle ATF in these applications except where noted in the Specifications and Approvals section.

Mobil ATF Multipurpose D/M is suitable for use in many passenger vehicles including:

- Ford
- GM
- Honda
- Hyundai
- Kia
- Mitsubishi
- Nissan
- Saab

- Toyota

Specifications and Approvals

This product is recommended for use in applications requiring:

ALLISON C-4 Application Suitable

FORD MERCON

GM DEXRON II D

GM DEXRON IIE

GM DEXRON III H

GM Type A Suffix A

Hyundai PSF-3

Kia PSF-3

Mitsubishi PS Fluid

NISSAN PSF-II

SAAB K0209A0080

TOYOTA PSF Type EH

Properties and Specifications

Property	
Kinematic Viscosity 40 C, cSt, ASTM D445	36
Pour Point, °C, ASTM D5950	-51
Density @ 15 C, g/cm ³ , ASTM D4052	0.857
Kinematic Viscosity 100 C, cSt, ASTM D445	7.1
Brookfield Viscosity @ -40 C, mPa.s, ASTM D2983	17500
Flash Point, Cleveland Open Cup, °C, ASTM D92	210
Color, Visual	Red

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

06-2023

ExxonMobil (China) Investment Co. Ltd
17th Floor, Metro Tower
30 Tian Yao Qiao Road
Shanghai 2000030
China

+86 21 24076000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved