



Mobil 1™ FS 0W-30

Mobil Passenger Vehicle Lube , 中国

Advanced Full Synthetic Motor Oil

Product Description

Mobil 1™ is the world's leading synthetic motor oil brand delivering our ultimate performance and protection.

Mobil 1 FS 0W-30 is an advanced full synthetic engine oil designed delivering great engine performance beyond conventional engine oils. Mobil 1 FS 0W-30 is engineered for the latest gasoline and diesel (without Diesel Particulate Filters or DPFs) engine technology delivering excellent all-round performance. It provides exceptional cleaning power, wear protection and overall performance even during longer oil change intervals. Mobil 1 FS 0W-30 keeps your engine running like new in all driving conditions.

Features and Benefits

Mobil 1 FS 0W-30 is engineered with a proprietary blend of ultra high performance synthetic basestocks fortified with a precisely balanced component additive system.

Features
▪ Successfully challenged 18,000 KMs Oil Drain Interval*
▪ Keep your engine running like new
▪ Ultimate Engine Performance and Wear Protection
▪ Enhanced Frictional Properties, Aids Fuel Economy
▪ Helps start-up in the low temperature
▪ Protects engines working under high temperatures
▪ Excellent engine cleanliness under variable fuels

Applications

Mobil 1 FS 0W-30 is recommended for many types of modern vehicles where it will help provide the performance required even under very demanding driving conditions.

- Latest diesel and gasoline (without DPF) engine technologies including high performance, turbo-charged, direct injection, and hybrids found in passenger cars, SUVs, light vans and trucks
- Most operating conditions, from mild to extreme

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product has the following approvals:
VW 502 00

This product has the following approvals:

VW 505 00

MB-Approval 229.3

MB-Approval 229.5

This product is recommended for use in applications requiring:

API CF

This product meets or exceeds the requirements of:

ACEA A3/B3

API SL

ACEA A3/B4

API SN Engine Test Requirements

Properties and Specifications

Property	
Pour Point, °C, ASTM D97	-48
Flash Point, °C, ASTM D92	228
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3.6
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	12.2
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	67
Viscosity Index, ASTM D2270	182
Mini-Rotary Viscometer, Apparent Viscosity, -40 C, mPa.s, ASTM D4684	20800
Ash, Sulfated, mass%, ASTM D874	1.3
Density @ 15 C, g/cm3, ASTM D4052	0.847
Total Base Number, mgKOH/g, ASTM D2896	12.6

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

01-2022

ExxonMobil (China) Investment Co. Ltd

17th Floor, Metro Tower
30 Tian Yao Qiao Road
Shanghai 2000030
China

+86 21 24076000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil  

© Copyright 2003-2022 Exxon Mobil Corporation. All Rights Reserved