



Mobil 1™ Formula 0W-40

Mobil Passenger Vehicle Lube , 中国

Advanced Full Synthetic Motor Oil

Product Description

Mobil 1™ Formula 0W-40 Advanced Full Synthetic Motor Oil is engineered for the latest gasoline and diesel engine technology (without GPFs or DPFs) delivering excellent all-round performance. It provides exceptional cleaning power, wear protection and overall performance.

Features and Benefits

Features	Advantages and Potential Benefits
Broad application	Meets or exceeds many OEM and industry approvals
Advanced full synthetic formulation	Excellent overall lubrication and wear protection
Excellent low temperature capabilities	Rapid engine protection at start-up to reduce engine wear.
Active cleaning agents	Help keep your engine run clean
Outstanding high temperature thermal and oxidative stability	Resists oil breakdown to provide long lasting power output

Applications

Mobil 1™ Formula 0W-40 is recommended for many types of modern vehicles where it will help provide unsurpassed performance under very demanding driving conditions, including:

- Latest engine technologies including Turbo-chargers, Direct Injection, Diesels (without GPFs or DPFs)
- High Performance Engines
- Helps to extend Oil Drain
- Nearly all operating conditions, from mild to extreme

Most operating conditions, from mild to extreme

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product has the following approvals:
MB-Approval 229.5
MB-Approval 229.3

This product has the following approvals:

VW 502 00

VW 505 00

This product is recommended for use in applications requiring:

API CF

VW 503 01

This product meets or exceeds the requirements of:

API SM

API SN

API SN PLUS

API SP

ACEA A3/B3

ACEA A3/B4

Fiat 9.55535-M2

Properties and Specifications

Property	
Grade	SAE 0W-40
Ash, Sulfated, mass%, ASTM D874	1.2
Flash Point, Cleveland Open Cup, °C, ASTM D92	230
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	78
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3.6
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	13.8
Density @ 15.6 C, g/ml, ASTM D4052	0.841
Viscosity Index, ASTM D2270	182
Total Base Number, mgKOH/g, ASTM D2896	12.5
Pour Point, °C, ASTM D97	-42
Mini-Rotary Viscometer, Apparent Viscosity, -40 C, mPa.s, ASTM D4684	30500

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2022

ExxonMobil (China) Investment Co. Ltd
17th Floor, Metro Tower
30 Tian Yao Qiao Road
Shanghai 2000030
China

+86 21 24076000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon Mobil  

© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved