



## Mobil Antifreeze/Coolant

Mobil Passenger Vehicle Lube , 中国

Mobil Passenger Vehicle Lube, High Performance Antifreeze/Coolant

### Product Description

Mobil Antifreeze/Coolant is a ready mixed high performance engine coolant for passenger and light duty vehicles.

### Features and Benefits

- Excellent Anti-boiling, Anti-freezing, and Anti-corrosion protection
- Widely applicable to many passenger cars, 4WD, and light duty vehicles (check vehicle service manual for special coolant requirements)
- Uses Organic Acid Technology (OAT), and is compatible with other similarly formulated OAT engine coolant technology
- Pre-diluted with water and needs no further water addition

### Applications

Mobil Antifreeze/Coolant is suitable for use in most passenger cars, 4WDs and light duty vehicles\*. The product is pre-diluted with good quality water, needing no further water addition, and does not contain any amine, borate, nitrite, phosphate or silicate corrosion inhibitor technology. It is fully compatible with other similarly formulated OAT engine coolants.

Extended service life of up to 5 years

\* Before using any coolant, please ensure that you have consulted your automobile owner's manual and your automobile manufacturer's recommendations prior to use.

### Specifications and Approvals

This product meets or exceeds the requirements of:	MOBIL -30°C ANTIFREEZE/COOLANT	MOBIL -45°C ANTIFREEZE/COOLANT
ASTM D3306	X	X
China GB 29743.1-2022	X	X
JIS K2234	X	X

### Properties and Specifications

Property	MOBIL -30°C ANTIFREEZE/COOLANT	MOBIL -45°C ANTIFREEZE/COOLANT
Boiling Point, C, ASTM D1120	107 min.	108.5 min.
Chloride Content, ppm, ASTM D3634	25 max.	25 max.
Color, Visual	Clear transparent red	Clear transparent red
Density @ 20C, g/cm3, SH/T 0068	1.065	1.080

Property	MOBIL -30°C ANTIFREEZE/COOLANT	MOBIL -45°C ANTIFREEZE/COOLANT
Freeze Point, C, ASTM D1177	-30 max.	-45 max.
pH, ASTM D1287	8.5	8.5

### Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise

03-2024

ExxonMobil (China) Investment Co. Ltd  
17th Floor, Metro Tower  
30 Tian Yao Qiao Road  
Shanghai 2000030  
China


+86 21 24076000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved