



Mobil Antifreeze/Coolant

Mobil Passenger Vehicle Lube , 中国

High Performance Antifreeze/Coolant

Product Description

Mobil Antifreeze/Coolant is a ready mixed high performance engine coolant for passenger and light duty vehicles.

Features and Benefits

- Excellent Anti-boiling, Anti-freezing, and Anti-corrosion protection
- Widely applicable to many passenger cars, 4WD, and light duty vehicles (check vehicle service manual for special coolant requirements)
- Uses Organic Acid Technology (OAT), and is compatible with other similarly formulated OAT engine coolant technology
- Pre-diluted with water and needs no further water addition

Applications

Mobil Antifreeze/Coolant is suitable for use in most passenger cars, 4WDs and light duty vehicles*. The product is pre-diluted with good quality water, needing no further water addition, and does not contain any amine, borate, nitrite, phosphate or silicate corrosion inhibitor technology. It is fully compatible with other similarly formulated OAT engine coolants.

Extended service life of up to 5 years

* Before using any coolant, please ensure that you have consulted your automobile owner's manual and your automobile manufacturer's recommendations prior to use.

Specifications and Approvals

Mobil Antifreeze/Coolant meets the requirements of:	Mobil -30°C Antifreeze/Coolant	Mobil -45°C Antifreeze/Coolant
China GB 29743-2013	X	X
ASTM D3306	X	X
JIS K2234	X	X

Typical Properties

	Mobil -30°C Antifreeze/Coolant	Mobil -45°C Antifreeze/Coolant
Color, Visual	Clear Transparent Red	Clear Transparent Red
Freezing Point (°C), ASTM D1177	-30 max.	-45 max.
Boiling Point (°C), ASTM D1120	107 min.	108.5 min.
Density @ 20°C, SH/T 0068	1.065	1.080
pH, ASTM D1287	8.5	8.5

	Mobil -30°C Antifreeze/Coolant	Mobil -45°C Antifreeze/Coolant
Chloride Content (ppm), ASTM D1881	25 max.	25 max.

Recommended shelf life for both products is 5 years, when stored undercover and away from moisture and direct sunlight.

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office or via the Internet, or will be provided by seller to customers if and as legally required. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design, and Mobilube, SHC are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

05-2020

ExxonMobil (China) Investment Co. Ltd

17th Floor, Metro Tower

30 Tian Yao Qiao Road

Shanghai 2000030

China

+86 21 24076000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil Esso XTO

© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved