



Mobil Super™ Conventional 10W-40

Mobil Passenger Vehicle Lube , 中国

Automotive Engine Oil

Product Description

Mobil Super™ Conventional 10W-40 is a high performance gasoline motor oil that deliver reliable engine protection and cleanliness.

Features and Benefits

- Helps reduce engine wear and corrosion
- Helps keep engine clean
- Multigrade motor oil allowing easier starts at low temperatures
- Good high temperature properties

Applications

Mobil Super™ Conventional 10W-40 is recommended for use in a wide range of applications and operating conditions. Suitable for use in passenger car application using gasoline, CNG or LNG.

Specifications and Approvals

This product meets or exceeds the requirements of:
API SM
API SN

Properties and Specifications

Property	
Grade	SAE 10W-40
Density @ 15 C, kg/l, ASTM D4052	0.868
Flash Point, Cleveland Open Cup, °C, ASTM D92	223
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3.8
Mini-Rotary Viscometer, Apparent Viscosity, -30 C, mPa.s, ASTM D4684	18000
Pour Point, °C, ASTM D97	-36
Ash, Sulfated, mass%, ASTM D874	0.8
Total Base Number, mgKOH/g, ASTM D2896	7
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	99

Property	
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	14.0

Health and safety

<http://www.msds.exxonmobil.com/psims/psims.aspx> Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2022

ExxonMobil (China) Investment Co. Ltd

17th Floor, Metro Tower

30 Tian Yao Qiao Road

Shanghai 2000030

China


+86 21 24076000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved