



Mobil™ full Syn (MT 60) 5W-30

Mobil Passenger Vehicle Lube , 中国

Full Synthetic Engine Oil

Product Description

Mobil™ full Syn (MT 60) 5W-30 is gasoline engine oils that deliver engine protection and cleanliness. Mobil™ full Syn (MT 60) 5W-30 is recommended for use in a wide range of applications and operating conditions.

Features and Benefits

- Helps reduce engine wear and corrosion
- Helps keep engine clean
- Multigrade motor oil allowing easier starts at low temperatures
- Good high temperature properties

Applications

Mobil™ full Syn (MT 60) 5W-30 is formulated to give you confidence of engine protection beyond that of conventional oils. We particularly recommend it for the following vehicle types and conditions:

- Passenger cars, SUV's
- Highway cruising
- Normal to occasionally severe operating conditions
- Stop and Go City Driving

Specifications and Approvals

This product meets or exceeds the requirements of:

API SM

API SN

Properties and Specifications

Property	
Grade	SAE 5W-30
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3.06
Flash Point, Cleveland Open Cup, °C, ASTM D92	223
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	62

Property	
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	10.1
Mini-Rotary Viscometer, Apparent Viscosity, -35 C, mPa.s, ASTM D4684	15500
Total Base Number, mgKOH/g, ASTM D2896	6.8
Density @ 15 C, kg/l, ASTM D4052	0.86
Pour Point, °C, ASTM D97	-36
Ash, Sulfated, mass%, ASTM D874	0.78
Viscosity Index, ASTM D2270	151

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

01-2024

ExxonMobil (China) Investment Co. Ltd

17th Floor, Metro Tower

30 Tian Yao Qiao Road

Shanghai 2000030

China

+86 21 24076000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon Mobil Esso XTO ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved