



## Mobil Delvac Legend™ 1330

Mobil Commercial Vehicle Lube , Colombia

High Performance Diesel Engine Oils

### Product Description

Mobil Delvac Legend 1320, 1330, 1340, and 1350 are high performance monograde diesel engine oils formulated from advanced technology base oils and a balanced additive system. They are specifically engineered for performance in intercooled, turbo-charged engines operating under severe on and off-highway conditions. Mobil Delvac Legend 1300 are used in a wide range of applications where a monograde lubricant is recommended.

### Features and Benefits

Features	Advantages and Potential Benefits
Excellent protection against oil thickening, high temperature deposits, sludge build-up, oil degradation and corrosion	Prolonged engine life Less wear Excellent protection against ring sticking
Extended TBN reserve	Long-term deposit/wear control Controls formation of acids when using higher sulfur fuels

### Applications

Naturally aspirated and turbo-charged diesel powered equipment

On highway light and heavy duty trucking

Off highway industries including: construction, mining, quarrying, and agriculture

Hydraulic system and wet breaks in mobile equipment where a SAE 20 diesel engine oil is required (Mobil Delvac Legend 1320)

Suitable for use on applications requiring MB 227 specification

### Specifications and Approvals

This product is recommended for use in applications requiring:
Allison C-4
API CF
API SF

### Properties and Specifications

Property	

Property	
Grade	SAE 30
Pour Point, °C, ASTM D97	-27
Viscosity Index, ASTM D2270	99
Flash Point, Cleveland Open Cup, °C, ASTM D92	235
Ash, Sulfated, mass%, ASTM D874	1.1
Total Base Number, mgKOH/g, ASTM D2896	10
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	101
Density @ 15 C, g/cm <sup>3</sup> , ASTM D4052	0.81
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	11.6

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2023

Organización Terpel S.A.

Address: Carrera 7 N° 75-51, Bogotá – Colombia

Phone: (57) 1 3267878

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**



© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved