



Mobil Delvac Xtreme Grease

Mobil Commercial Vehicle Lube , Colombia

Grease

Product Description

Mobil Delvac Xtreme Grease is an extra high performance extreme-pressure grease. It is an NLGI 2 grade and is manufactured with a proprietary, high-temperature lithium complex thickener system. It exhibits excellent resistance to softening under severe working and provides good adhesion and cohesion. An extreme-pressure additive provides exceptional protection against wear and shock loads, while additional additives enhance resistance to high-temperature oxidation and protection against rust. Other formulation features provide very good resistance to water wash, and long service in bearings operating at high temperatures. This heavy-duty, severe-service grease has outstanding structural stability and chemical stability, will not corrode steel or copper bearing alloys, and is compatible with conventional seal materials.

Mobil Delvac Xtreme Grease is recommended for use in heavy-duty trucks, especially hinge and bucket pins, U-joints, and fifth wheels. It is also recommended for construction and mining sector applications, particularly for the lubrication of plain and antifriction bearings in contractor and mining vehicles working under severe operating and weather conditions. Mobil Delvac Xtreme Grease is also recommended for use in heavily loaded industrial bearings. The recommended application temperature range is -20°C to +175°C.

Features and Benefits

Mobil Delvac Xtreme Grease is designed by our formulation technologists specifically to meet the needs of customers with heavily loaded equipment that requires high extreme-pressure/antiwear performance and stay-in-place performance even in tough conditions where water wash, high sliding, and high temperature conditions are present.

Features	Advantages and Potential Benefits
Excellent resistance to water, including spray off and wash out	Maintains excellent lubrication properties and protects equipment in conditions of water contamination
Outstanding extreme-pressure and antiwear protection	Lower maintenance costs and less unanticipated downtime
Better stay-put properties at high temperatures	Excellent performance in high shear, high load applications, especially where grease re-supply is limited
Excellent resistance to rust and corrosion	Protects equipment in the presence of water for reduced maintenance and longer equipment life

Applications

Recommended by ExxonMobil for use in:

- Heavy-duty trucks, especially hinge and bucket pins, U-joints, and fifth wheels
- Mining and construction equipment
- Highly loaded plain and antifriction industrial bearings

Properties and Specifications

Property	
Grade	NLGI 2

Property	
Base Oil Viscosity of Greases @ 40 C, mm ² /s, AMS 1697	320
Color, Visual	Orange
Copper Strip Corrosion, Rating, ASTM D4048	1A
Corrosion Preventive Properties, Rating, ASTM D1743	PASS
Dropping Point, °C, ASTM D2265	260
Four-Ball Wear Test, Scar Diameter, mm, ASTM D2266	0.5
Penetration, 60X, 0.1 mm, ASTM D217	280
Roll Stability, Penetration Consistency Change, 0.1 mm, ASTM D1831	-4
Timken OK Load, kg, ASTM D2509	40 (min)
Water Washout Loss, wt %, ASTM D1264	6

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

07-2022

Organización Terpel S.A.

Address: Carrera 7 N° 75-51, Bogotá – Colombia

Phone: (57) 1 3267878

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil Esso XTO

© Copyright 2003–2022 Exxon Mobil Corporation. All Rights Reserved