



Mobilube XFD Series

Mobil Commercial Vehicle Lube , Colombia

Extra High Performance Drivetrain Lubricants

Product Description

Mobilube XFD 50 and 60 are extra high performance drivetrain lubricants engineered specifically to provide optimum component life when used as recommended in Caterpillar final drives and axles. They are formulated from advanced base oils and the latest additive technology to protect bearings and gears from premature failure due to fatigue. These lubricants deliver excellent performance in heavy-duty commercial axles and final drives where extreme pressures and shock loading are expected. They provide exceptional chemical and thermal stability at elevated bulk oil temperatures generated under heavy loads and/or high ambient temperatures.

Mobilube XFD Series have been extensively field tested in Caterpillar off-highway heavy trucks and bulldozers over a wide range of ambient temperatures and operating in severe conditions with a recommended drain interval up to 4,000 hours for off-highway haulers.

Features and Benefits

Demands for higher productivity, more severe operating conditions, and larger capacity equipment put severe stress on axles and final drive components. In severe applications, TO-4 lubricants may be limited in terms of wear protection in heavily loaded final drives due to their need to also serve the frictional requirements of clutches in heavy-duty transmissions. For optimum durability and performance, Mobilube XFD gear lubricants can be relied on to maintain productivity and minimize maintenance costs between scheduled service intervals in extreme applications. The key benefits include:

| Features | Advantages and Potential Benefits |
|---|---|
| Improved extreme pressure (EP) performance versus TO-4 fluids | Increased load and shock carrying ability with reduced premature failures and operating costs |
| High oxidation and thermal stability | Longer oil life, reduced deposits, and extended component life |
| Excellent protection against copper corrosion and rust | Extended component life and lower maintenance costs |
| Wide temperature capability | Simplifies inventory and reduces need for seasonal change-outs |
| Good compatibility with seals and conventional drive train lubricants | Reduces leakage and contamination from external sources |
| Eliminates or reduces foaming | Maintains film strength for reliable wear protection |

Applications

Recommended by ExxonMobil for use in:

- Heavy-duty axles and final drives used in trucks and bulldozers built by Caterpillar
- Off-highway industries including: construction, mining, and quarrying
- Applications where the maximum operating ambient temperature is below 32°C (90°F)
- Applications where the maximum operating ambient temperature is below 50°C (122°F)
- Not recommended for engines, transmissions or hydraulic systems
- Not recommended for final drives and axles containing friction material and/or wet brakes

Specifications and Approvals

| This product meets or exceeds the requirements of: | 50 | 60 |
|--|----|----|
| CATERPILLAR FD-1 | X | X |

Properties and Specifications

| Property | 50 | 60 |
|--|--------|--------|
| Grade | SAE 50 | SAE 60 |
| Density @ 15 C, kg/l, ASTM D4052 | 0.897 | 0.899 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 250 | 255 |
| Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445 | 18.4 | 25.2 |
| Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445 | 206 | 334 |
| Pour Point, °C, ASTM D97 | -24 | -15 |
| Viscosity Index, ASTM D2270 | 97 | 97 |

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

01-2022

Organización Terpel S.A.

Address: Carrera 7 N° 75-51, Bogotá – Colombia

Phone: (57) 1 3267878

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil Esso XTO

© Copyright 2003-2022 Exxon Mobil Corporation. All Rights Reserved