



## Mobil Vacuum™ Pump Oil

Mobil Industrial , Colombia

Mobil Industrial

### Product Description

Mobil Vacuum Pump Oil is a premium lubricant, blended from specific high quality mineral oil with low volatility characteristics, for the lubrication of vacuum pumps

Mobil Vacuum Pump Oil has a high degree of chemical stability enabling it to resist oxidation and the subsequent formation of sludge and deposits, an essential characteristic in all cases where continuous service is involved. This enables the oil to retain its original properties such as viscosity and demulsibility and so prolong service life.

Water vapour is a common contaminant in vacuum systems and tends to condense in pumps, oils separators and reservoirs. Mobil Vacuum Pump Oil has demulsibility to separate readily from water. This aids water removal and prevents its return to metal surfaces to cause rust and corrosion.

### Features and Benefits

Mobil Vacuum Pump Oil offers the following benefits:

- Low volatility characteristics.
- Good air release properties to provide efficient pump operation.
- Good demulsibility to separate quickly from water and resist emulsion formation.
- Good wear protection under start-up and boundary conditions.
- Long service life due to high level of chemical and thermal stability and freedom from deposit formation.

### Applications

The oil is especially formulated for use in vacuum pumps where it will tolerate exposure to very high vacuums with low levels of evaporation. Mobil Vacuum Pump Oil resists the formation of deposits and maintains its original lubricating properties over a long life. It is a dehydrated oil; therefore, keep containers well sealed to prevent contamination by moisture.

It is also suitable for use in pump bearings and sealing glands.

### Properties and Specifications

Property	
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	8.26
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	68.5
Appearance, AMS 1738	Clear and Bright

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

02-2021

Organización Terpel S.A.

Address: Carrera 7 N° 75-51, Bogotá – Colombia

Phone: (57) 1 3267878

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved