



Mobil Super™ 2000 10W-30

Mobil Passenger Vehicle Lube , Colombia
Premium Semi-Synthetic Passenger Vehicle Engine Oil

Product Description

Mobil Super 2000 10W-30 is an enhanced-premium semi-synthetic motor oil meeting the latest industry engine oil specifications. It is designed to provide an ex level of protection and performance under the most demanding conditions.

Features and Benefits

Mobil Super 2000 products are industry proven so you can trust you will get the performance you want from your vehicle. Mobil Super 2000 10W-30 contain friction semi-synthetic formulation which increases engine efficiency and offers greater fuel economy. Mobil Super 2000 10W-30 helps to promote long engine life

Mobil Super 2000 provides:

- Thanks to its semi-synthetic formulation provides improved fuel economy up to a 3%* by enabling the engine to work more efficiently
- Its additive package provides excellent protection against engine wear and deposit formation.
- Provides superior engine protection during start up
- Excellent high temperature protection thanks to its high quality base oil formulation

Applications

Mobil Super 2000 10W-30 products is formulated to give you confidence of protection beyond that of conventional oils. We particularly recommend it for the foll vehicle types and conditions:

- Latest gasoline engine technologies
- Passenger cars, SUV's, light trucks and vans
- Stop and Go City Driving
- Normal to severe operating conditions
- Turbo-Chargers
- High Performance Engines

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle

Specifications and Approvals

This product is recommended for use in applications requiring:
GM 6094M
This product meets or exceeds the requirements of:
API SJ
API SL
API SM

This product meets or exceeds the requirements of:

API SN

API SN PLUS

API SN PLUS RESOURCE CONSERVING

API SN Resource Conserving

API SP

API SP Resource Conserving

ILSAC GF-6A

Chrysler MS-6395

Properties and Specifications

Property	
Grade	SAE 10W-30
Pour Point, °C, ASTM D97	-39
Flash Point, Cleveland Open Cup, °C, ASTM D92	228
Ash, Sulfated, mass%, ASTM D874	0.8
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3.1
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	69
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	10.4
Density @ 15.6 C, g/ml, ASTM D4052	0.86
Viscosity Index, ASTM D2270	138

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

03-2021

Organización Terpel S.A.

Address: Carrera 7 N° 75-51, Bogotá – Colombia

Phone: (57) 1 3267878

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All properties may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

Exxon

Mobil

Esso

XTOL

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved