



Mobil Super™ 2000 5W-20

Mobil Passenger Vehicle Lube , Colombia
Premium Semi-Synthetic Passenger Vehicle Engine Oil

Product Description

Mobil Super™ 2000 5W-20 is an enhanced-premium semi-synthetic motor oil meeting the latest industry engine oil specifications. It is designed to provide an ex level of protection and performance under the most demanding conditions

Features and Benefits

Mobil Super™ 2000 5W-20 is industry proven so you can trust you will get the performance you want from your vehicle. It contains low friction semi-syn formulation which increases engine efficiency and offers greater fuel economy. The American Petroleum Institute (API) classifies the 5W-20 viscosity grade as "Re Conserving" engine lubricant and meets or exceeds ILSAC GF-5 / API SN Plus. Those claims are backward compatible with earlier performance levels such as A SM, SL, and SJ and previous ILSAC categories.

Mobil Super™ 2000 5W-20 provides:

- Helps to promote long engine life.
- Its additive package provides excellent protection against engine wear and deposit formation.
- Provides superior engine protection during start up
- Excellent high temperature protection thanks to its high quality base oil formulation

Applications

Mobil Super™ 2000 5W-20 is formulated to give you confidence of protection beyond that of conventional oils. We particularly recommend it for the following types and conditions:

- Latest gasoline engine technologies
- Passenger cars, SUV's, light trucks and vans
- Stop and Go City Driving
- Normal to severe operating conditions
- Turbo-Chargers
- High Performance Engines

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product is recommended for use in applications requiring:
Ford WSS-M2C930-A
This product meets or exceeds the requirements of:
API SJ
API SL
API SM

This product meets or exceeds the requirements of:

API SN

API SN PLUS

API SN PLUS Resource Conserving

API SN Resource Conserving

API SP

API SP Resource Conserving

ILSAC GF-6A

Chrysler MS-6395

Ford WSS-M2C945-A

Ford WSS-M2C945-B1

Ford WSS-M2C960-A1

Properties and Specifications

Property	
Grade	SAE 5W-20
Viscosity Index, ASTM D2270	146
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	8.3
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	49
Pour Point, °C, ASTM D97	-42
Flash Point, Cleveland Open Cup, °C, ASTM D92	226
Density @ 15 C, g/ml, ASTM D4052	0.86

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

12-2021

Organización Terpel S.A.

Address: Carrera 7 N° 75-51, Bogotá – Colombia

Phone: (57) 1 3267878

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

Exxon

Mobil

Esso


ExxonMobil

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved