



Mobil Super™ Synthetic Euro 5W-40

Mobil Passenger Vehicle Lube , Colombia  
Premium Full Synthetic Passenger Vehicle Engine Oil

Product Description

Mobil Super Synthetic Euro 5W-40 is a premium full synthetic engine oil, designed to provide outstanding levels of protection for modern vehicles in city driving.

Features and Benefits

Mobil Super Synthetic Euro 5W-40 is industry proven so you can enjoy the freedom and convenience of driving with engine well protected from harsh conditions driving.

Mobil Super Synthetic Euro 5W-40 provides:

- Outstanding wear protection
- Outstanding engine cleanliness
- Outstanding high temperature protection
- Outstanding low temperature protection

Applications

Mobil Super Synthetic Euro 5W-40 is formulated to give you confidence of protection beyond that of conventional or semi-synthetic oils. We particularly recomme product if you regularly experience demanding conditions where it can help combat the damage caused by frequent high engine stress:

- Nearly all engine technologies
- Gasoline and Diesel
- Passenger cars, SUV's, light trucks and vans
- Highway cruising and stop and go city driving
- Normal to frequently severe operating conditions
- Turbo-Chargers and Direct Injection engines
- High Performance Engines

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product has the following approvals:
BMW Longlife 01
MB-Approval 229.3
MB-Approval 229.5
Peugeot/Citroën Automobiles B71 2296
Porsche A40
RENAULT RN0700

<b>This product has the following approvals:</b>
RENAULT RN0710

<b>This product meets or exceeds the requirements of:</b>
API SJ
API SL
API SM
API SN
ACEA A3/B3
ACEA A3/B4
API CF
VW 502 00
VW 505 00

Properties and Specifications

Property	
Grade	SAE 5W-40
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	13.0
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	70
Viscosity Index, ASTM D2270	173
Density @ 15 C, g/ml, ASTM D4052	0.853
Pour Point, °C, ASTM D97	-39
Flash Point, Cleveland Open Cup, °C, ASTM D92	238
Ash, Sulfated, mass%, ASTM D874	1.1
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3.8

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>  
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

07-2022  
Organización Terpel S.A.  
Address: Carrera 7 N° 75-51, Bogotá – Colombia  
Phone: (57) 1 3267878

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil

Esso

XtO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved