Mobil Special 4T 20W50 Page 1 of 2



# Mobil Special 4T 20W50

Mobil Passenger Vehicle Lube, Colombia

Multigrade oil for four-stroke motorcycle engines

## **Product Description**

Mobil Special 4T 20W-50 is a high performance mineral oil for four-stroke motorcycle engines, designed primarily for general use in many types of motorcycles and four-stroke engines.

#### Features and Benefits

Mobil Special 4T 20W-50 oil combines highly refined mineral oils and an advanced additive system to provide good engine cleanliness, good protection against wear and corrosion protection.

## Key features and benefits include:

Features	Advantages and Potential Benefits
Good protection against wear	Helps extend engine life
Thermal and antioxidant stability	Helps keep engines clean to provide a smoother operation
Good corrosion protection	Protects critical engine components

## Specifications and Approvals

This product is recommended for use in applications requiring:	
API SF	

#### **Properties and Specifications**

Property	
Grade	SAE 20W-50
Ash, Sulfated, mass%, ASTM D874	0,95
Density @ 15.6 C, g/ml, ASTM D4052	0,8911
Flash Point, Cleveland Open Cup, °C, ASTM D92	230
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	17.2
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	146.1
Pour Point, °C, ASTM D97	-24
Total Base Number, mgKOH/g, ASTM D2896	8.2

Mobil Special 4T 20W50 Page 2 of 2

#### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ http://www.msds.exxonmobil.com/psims/psims.aspx

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2020

Organización Terpel S.A.

Address: Carrera 7 N° 75-51, Bogotá – Colombia

Phone: (57) 1 3267878

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

