



## Mobil Super 4T MX 10W-40

Mobil Passenger Vehicle Lube , Colombia

Mobil passenger-vehicle-lube Semi-Synthetic High Performance Four-Stroke Motorcycle Engine Oil

### Product Description

Mobil Super 4T MX 10W-40 is a high performance semi-synthetic four-stroke motorcycle engine oil primarily intended for general use in many types of four-stroke motorcycles and engines. It's unique formulation provides excellent flow characteristics to reduce engine wear during start-up and outstanding protection of the transmission and the clutch during operation.

### Features and Benefits

Mobil Super 4T MX 10W-40 provides good engine cleanliness, good wear protection and corrosion protection. Key features and benefits include:

- Provides anti-wear protection to help promote long engine and transmission life
- Helps keep your engine cleaner
- Formulated with premium base stocks for increased oxidation stability and less volatility.
- Excellent frictional properties for proper performance of the clutch.

### Applications

Mobil Super 4T MX 10W-40 oil is a product of an advanced blend of mineral and synthetic bases recommended for 4-stroke motorcycle in which the manufacturer specifies the use of SAE 10W-40. Its formulation provides the adequate level of protection for the engine transmission and clutch, particularly in air-cooled engines, which tend to operate at higher temperatures. It is also especially recommended for 4-stroke engines equipped with catalytic converters to reduce emissions. It is recommended by ExxonMobil for applications requiring API SL oils. Meets or exceeds the latest JASO MA performance standard.

### Specifications and Approvals

<b>This product meets or exceeds the requirements of:</b>
API SL
JASO MA
JASO MA2

### Properties and Specifications

Property	
Grade	SAE 10W-40
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	95.37
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	14
Pour Point, °C, ASTM D97	-30
Ash, Sulfated, mass%, ASTM D874	0.78

Property	
Flash Point, °C, ASTM D92	220
Density @ 15.6 C, g/ml, ASTM D4052	0.87

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2021

Organización Terpel S.A.

Address: Carrera 7 N° 75-51, Bogotá – Colombia

Phone: (57) 1 3267878

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExxonMobil**

Exxon Mobil Esso XTO

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved