



Mobil™ Agri Extra 10W-40

Mobil Commercial Vehicle Lube , Germany

Super Tractor Oil Universal (STOU) Lubricant

Product Description

Mobil™ Agri Extra 10W-40 is a synthetic blend, extra high performance, multi-functional lubricant for most farm equipment applications. This STOU lubricant provides excellent performance in diesel and gasoline engines, transmissions, hydraulics, final drives, and oil-immersed brakes operating in agricultural service. It is engineered using high quality base stocks and an optimised additive system. Mobil Agri Extra 10W-40 lubricant is recommended for use in a wide range of severe duty applications and extreme operating environments found in the farming industry.

Features and Benefits

Agricultural enterprises employ a wide variety of equipment requiring multi-functional lubrication performance. The advanced technology in Mobil Agri Extra 10W-40 meets the diverse lubrication requirements of this equipment, which reduces the number of lubricants required, and the possibility of misapplication. The key benefits include:

| Features | Advantages and Potential Benefits |
|---|---|
| Reduced sludge build-up and high temperature deposits | Excellent thermal and oxidation stability |
| TBN reserves | Improved deposit control |
| Good rust and corrosion protection | Reduced wear and long equipment life especially in hydraulic components |
| Effective detergency/dispersancy | Cleaner engines and long engine life |
| High temperature viscosity retention and volatility control | Reduced engine scuffing, bore polishing, and oil consumption |
| Effective frictional and load carrying properties | Increased power, improved power train performance, and elimination of chatter in wet brakes |
| Excellent low temperature pumpability and performance | Easier engine start-up, reduced wear in critical valve train and good hydraulic response |
| Component compatibility | Longer gasket and seal life |
| Multipurpose product | Reduces inventory and chance for misapplication |

Applications

- Mixed diesel and gasoline-powered farm vehicles and equipment
- Farm equipment transmissions and power systems requiring multifunctional fluid

Specifications and Approvals

| |
|---|
| This product has the following approvals: |
| ZF TE-ML 07B |
| ZF TE-ML 06B (*) |

| |
|--|
| This product is recommended for use in applications requiring: |
|--|

| | |
|--|--|
| This product is recommended for use in applications requiring: | |
| ACEA E3 | |
| Allison C-4 | |
| API CE | |
| API CF | |
| API CF-4 | |
| API CG-4 | |
| API GL-4 | |
| API SF | |
| Caterpillar TO-2 | |
| CNH MAT 3525 | |
| CNH MAT 3526 | |
| Ford ESEN-M2C86-B | |
| FORD ESN-M2C134-D | |
| Ford ESN-M2C159-B | |
| JICASE MS 1206 | |
| JICASE MS 1207 | |
| JICASE MS 1209 | |
| JOHN DEERE JDM J27D | |
| MASSEY FERGUSON CMS M1139 | |
| MASSEY FERGUSON CMS M1144 | |
| MASSEY FERGUSON CMS M1145 | |

| | |
|--|--|
| This product meets or exceeds the requirements of: | |
| JOHN DEERE JDM J20C | |

Properties and Specifications

| Property | |
|--|------------|
| Grade | SAE 10W-40 |
| Cold-Cranking Simulator, Apparent Viscosity @ -25 C, mPa.s, ASTM D5293 | 6600 |
| Brookfield Viscosity @ -40 C, mPa.s, ASTM D2983 | 131000 |
| Viscosity Index, ASTM D2270 | 146 |

| Property | |
|---|------|
| Total Base Number, mgKOH/g, ASTM D2896 | 12 |
| Pour Point, °C, ASTM D97 | -42 |
| Kinematic Viscosity @ 40 C, mm2/s, ASTM D445 | 93 |
| Kinematic Viscosity @ 100 C, mm2/s, ASTM D445 | 13.5 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 229 |
| Density @ 15 C, g/ml, ASTM D1298 | 0.86 |
| Ash, Sulfated, mass%, ASTM D874 | 2 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

07-2021
EXXONMOBIL LUBRICANTS & SPECIALTIES EUROPE, A DIVISION OF EXXONMOBIL PETROLEUM & CHEMICAL, BVBA (EMPC)
POLDERDIJKWEG
B-2030 Antwerpen
Belgium

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.mobil.com.de/de-de/kontakt>
Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect pro performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without nc All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intende override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entit

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved