



Mobil Delvac XHP™ ESP 10W-40

Mobil Commercial Vehicle Lube , Ecuador

Emission System Protection Diesel Engine Oil

Product Description

Mobil Delvac XHP ESP 10W-40 is a synthetic extra high performance diesel engine oil engineered to provide lubrication to modern, high performance, low em engines used in severe applications. This engine oil is designed using high performance base oils which provide excellent low temperature fluidity, high tempe viscosity retention and volatility control. The new advanced additive system has been expertly engineered to help towards long engine life¹ and maintain the efficie emission reduction systems including the Diesel Particulate Filter (DPF). Its specifications and approvals allow Mobil Delvac XHP ESP 10W-40 to target mixe applications.

(1) Well formulated oils, like Mobil Delvac, that meet or exceed industry or OEM specifications, can help protect engines. Consult OEM for optimum fluid selection. results may vary depending on OEM requirements, type of engine and its maintenance, application and service conditions, and prior lubricant used.

Features and Benefits

High output, low emission engines significantly increase demands on engine lubricants. Tighter engine design, use of inter-coolers, and turbochargers increase th stresses on the lubricant. Low emission engine technologies such as higher fuel injection pressure, retarded timing and aftertreatment devices all require impro performance in areas such as oxidation stability, soot dispersancy, volatility and compatibility with aftertreatment devices. The advanced technology in Mobil Delva ESP 10W-40 delivers exceptional performance, long drain interval capability and protection of exhaust systems including those fitted with Diesel Particulate Filters The key benefits include:

¹ Well formulated oils, like Mobil Delvac, that meet or exceed industry or OEM specifications, can help protect engines. Consult OEM for optimum fluid selection. results may vary depending on OEM requirements, type of engine and its maintenance, application and service conditions, and prior lubricant used.

Features	Advantages and Potential Benefits
Outstanding protection against oil thickening, high temperature deposits, sludge build-up and, oil degradation	Provides capability for long drain intervals Helps to protect against ring sticking
Excellent anti-wear, anti-scuff properties and bore polishing and corrosion protection.	Helps to towards long engine life ¹
Stay-in-grade shear stability. Very low volatility	Helps to reduce viscosity breakdown and oil consumption under heavy duty, temperature operating conditions
Low ash, sulfur and phosphorous levels	Helps to protect exhaust systems devices like those fitted with DPF
Excellent low temperature properties	Helps to improve pumpability and oil circulation

Applications

- Heavy Duty Diesel Engines including Euro V/VI Modern Low Emissions Vehicles, Utilizing Technologies such as Diesel Particulate Filter (DPF), Selective C_x Reduction (SCR), Continuously Regenerating Traps (CRT), Diesel Oxidation Catalysts (DOC) and Exhaust Gas Recirculation (EGR)
- Heavy Duty Diesel Engines using low sulfur diesel fuels and many biodiesel fuel formulations
- Naturally Aspirated and Turbo-Charged Diesel Powered Equipment
- On-Highway Short-Haul and Long-Haul Trucks and Buses
- Off-Highway Mining, Construction and Agricultural Equipment

(2) Please refer to the owners handbook for OEM application requirements and oil drain intervals for your vehicle or equipment

Specifications and Approvals

This product has the following approvals:

Mack EO-O Premium Plus

MACK EOS-4.5

MAN M 3271-1

MAN M 3477

MAN M 3775

MB-Approval 228.51

MTU Oil Category 3.1

RENAULT TRUCKS RLD-2

RENAULT TRUCKS RLD-3

VOLVO VDS-3

VOLVO VDS-4

VOLVO VDS-4.5

This product is recommended for use in applications requiring:

MAN M 3575

MAN M 3477

This product meets or exceeds the requirements of:

API CH-4

API CI-4

API CI-4 PLUS

API CJ-4

API CK-4

JASO DH-2

ACEA E4

ACEA E6

ACEA E7

ACEA E9

Caterpillar ECF-3

This product meets or exceeds the requirements of:	
Cummins CES 20081	
Cummins CES 20086	
DAF Extended Drain	
ISUZU DEO (w/ DPD Equipped Vehicles)	

Properties and Specifications

Property	
Density @ 15.6 C, kg/l, ASTM D4052	0.8613
Flash Point, Cleveland Open Cup, °C, ASTM D92	232
Pour Point, °C, ASTM D97	-30
Viscosity Index, ASTM D2270	153
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	13.7
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	91

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

12-2021
TERPEL-LUBRICANTES ECUADOR S.A.S.

Av. Joaquin Orrantia 125 y Av. de las Américas, Edificio Solaris, Piso 12, Oficinas 801-812, Guayaquil, Ecuador
Teléfono: (593) 4-3811980

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect pro performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without nc All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intende override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entit

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved