



Mobil Delvac™ 1 Transmission Fluid V50

Mobil Commercial Vehicle Lube , Ecuador

Mobil Commercial Vehicle Lubricant

Product Description

Mobil Delvac™ 1 Transmission Fluid V50 is a fully synthetic, heavy duty manual transmission lubricant engineered to meet demanding requirements. Recommended by ExxonMobil for year-round lubrication of manual transmissions requiring Volvo 97315 or Volvo 97319 type oils (refer to owner's manual recommendation) for on-highway commercial medium and heavy duty trucking, including vocational applications, heavy load hauling, and frequent PTO usage. Designed to provide excellent performance, Mobil Delvac 1 Transmission Fluid V50 incorporates the latest lubrication technology based on synthetic basestocks and an advanced additive system providing significant advantages over conventional transmission oils. This advanced additive system provides outstanding detergency and dispersancy with optimized protection against thermal degradation, oxidation, wear, and corrosion. Because of its high viscosity index and synthetic base oil mixture, it provides stronger film strength at higher temperatures than conventional oils. This technology also ensures effective lubrication at extremely low temperatures without oil channeling. Mobil Delvac 1 Transmission Fluid V50 is recommended for manual transmissions and non-hypoid gear-box applications.

Features and Benefits

Features	Advantages and Potential Benefits
Excellent load carrying, anti-wear, and extreme pressure (EP) performance	Helps to protect against wear under harsh operating conditions throughout the transmission life
Outstanding protection against deposit formation	Contributes to long seal life, extended drain, and service intervals
High protection from corrosion of copper and its alloys	Helps to protect and extend the life of synchronizers while delivering smoother shifting performance
Optimized thermal and oxidation protection	Contributes to extended drain and service intervals for controlled maintenance costs
Exceptional shear stability	Helps to maintain effective viscosity and film strength for better wear protection during severe operation
Outstanding low temperature fluidity	Contributes to quicker starts, easy shifting and helps to reduce wear during cold temperature start-ups
Extended drain and service interval capability	Helps to reduce operating costs and contributes to improved productivity
Optimized and stable friction properties	Contributes to smooth and rapid gear shifting

Applications

Recommended by ExxonMobil for use in:

- Heavy duty manual transmissions, specifically those requiring Volvo 97315 or Volvo 97319 type oils (refer to owner's manual recommendation)
- On-highway commercial medium and heavy duty trucking, including vocational applications, heavy load hauling, and frequent PTO usage
- Applications in regions where severe winter temperatures are encountered
- Applications where extended service intervals and warranties are required
- Association with Mobil Delvac synthetic gear oils in rear axles for exceptional drivetrain efficiency and fuel economy improvement
- NOT suitable for hypoid gear applications in differentials and final drives, either for topping-off or refills, where API service GL-5 or MIL-PRF-2105E lubricants are specified in the owner's manual.

Specifications and Approvals**This product has the following approvals:**

VOLVO 97315

VOLVO 97319

This product is recommended for use in applications requiring:

API GL-4

Properties and Specifications

Property	
Grade	SAE 75W-90
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	17.8
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	115
Viscosity Index, ASTM D2270	172
Pour Point, °C, ASTM D97	-42
Flash Point, °C, ASTM D92	252
Density @ 15.6 C, g/ml, ASTM D4052	0.85

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

03-2021

Terpel-Comercial Ecuador Compañía Limitada

Dirección : Av. Joaquín Orrantía, Edificio Solaris, Piso 12, Oficinas (801-812), Guayaquil – Ecuador

Teléfono: +593 42634060

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved