



Mobil Special™ 20W-50

Mobil Passenger Vehicle Lube , Ecuador

Mobil passenger-vehicle-lube

Product Description

Mobil Special™ 20W-50 is a premium quality mineral motor oil. The product is designed to provide protection for your engine under most operating conditions.

Features and Benefits

Mobil Special™ 20W-50 provides engine protection and helps promote long engine life.

- Extended protection against engine wear and deposits formation
- Engine protection during start up
- Helps combat sludge

Applications

Mobil Special™ 20W-50 has been formulated to be suitable for use in vehicles requiring an API SL claim. ExxonMobil particularly recommends Mobil Special 20W-50 for daily driving under normal conditions:

- Passenger cars, SUV's, light trucks and vans (Gasoline engines) requiring an API SL
- Normal operating conditions
- Suitable for use under a wide range of temperature conditions

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product meets or exceeds the requirements of:

API SL

JASO MA

JASO MA2

Properties and Specifications

Property	

Property	
Grade	SAE 20W-50
Density @ 15.6 C, g/ml, ASTM D1298	0.88
Viscosity Index, ASTM D2270	136
Total Base Number, mgKOH/g, ASTM D2896	5.9
Pour Point, °C, ASTM D97	-30
Flash Point, Cleveland Open Cup, °C, ASTM D92	231
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	138
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	17.2

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2023

TERPEL-LUBRICANTES ECUADOR S.A.S.


Av. Joaquín Orrantía 125 y Av. de las Américas, Edificio Solaris, Piso 12, Oficinas 801-812, Guayaquil, Ecuador

Teléfono: (593) 4-3811980

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003–2024 Exxon Mobil Corporation. All Rights Reserved