



## Mobil Super™ 2000 5W-30

Mobil Passenger Vehicle Lube , Ecuador

Premium Semi-Synthetic Passenger Vehicle Engine Oil

### Product Description

Mobil Super™ 2000 5W-30 is an enhanced-premium semi-synthetic motor oil meeting the latest industry engine oil specifications. It is designed to provide an excellent level of protection and performance under the most demanding conditions.

### Features and Benefits

Mobil Super™ 2000 5W-30 is industry proven so you can trust you will get the performance you want from your vehicle. Mobil Super 2000 5W-30 contains low friction semi-synthetic formulation which increases engine efficiency and offers greater fuel economy.

Mobil Super™ 2000 5W-30 provides:

- Helps to promote long engine life
- Thanks to its semi-synthetic formulation provides improved fuel economy up to a 3%\* by enabling the engine to work more efficiently
- Its additive package provides excellent protection against engine wear and deposit formation.
- Provides superior engine protection during start up
- Excellent high temperature protection thanks to its high quality base oil formulation

\*Potential fuel economy improvement obtained by switching from the most common higher viscosity oils to a lower viscosity grade, based on M111FE data by independent test lab. Actual savings are dependent upon vehicle/engine type, outside temperature, driving conditions and your current engine oil viscosity.

### Applications

Mobil Super™ 2000 5W-30 products is formulated to give you confidence of protection beyond that of conventional oils. We particularly recommend it for the following vehicle types and conditions:

- Latest gasoline engine technologies
- Passenger cars, SUV's, light trucks and vans
- Stop and Go City Driving
- Normal to severe operating conditions
- Turbo-Chargers
- High Performance Engines

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

### Specifications and Approvals

**This product is recommended for use in applications requiring:**

Fiat Chrysler Automotive MS-6395

**This product is recommended for use in applications requiring:**

Ford WSS-M2C929-A

GM 6094M

**This product meets or exceeds the requirements of:**

API SJ

API SL

API SM

API SN

API SN PLUS

API SN PLUS RESOURCE CONSERVING

API SN Resource Conserving

Ford WSS-M2C946-A

Ford WSS-M2C946-B1

**Properties and Specifications**

Property	MOBIL SUPER 2000 5W-30
Grade	SAE 5W-30
Viscosity, ASTM D445	
cSt@40°C	63
cSt@ 100°C	10.4
Cold-Cranking Simulator, Apparent Viscosity @ -30 C	6200
ViscosityIndex,ASTMD2270	153
Ash,Sulfated, mass%,ASTMD874	0.84
Hi-TempHi-ShearViscosity@150C,mPa.s,ASTM D4683	3.11
Pour Point,°C,ASTMD97	-42
FlashPoint,ClevelandOpenCup,°C, ASTMD92	220
Density@15C,g/ml,ASTM D4052	0.9

**Health and safety**

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

03-2021

23.09.2021

Terpel-Comercial Ecuador Compañía Limitada

Dirección : Av. Joaquín Orrantía, Edificio Solaris, Piso 12, Oficinas (801-812), Guayaquil – Ecuador

Teléfono: +593 42634060

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExxonMobil**

Exxon Mobil  

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved