



Mobil Super™ Multigrado 20W-50

Mobil Passenger Vehicle Lube , Ecuador

Premium Multigrade Passenger Vehicle Engine Oils

Product Description

Mobil Super™ Multigrado 20W-50 is a premium quality mineral motor oil meeting the latest industry engine oil specifications. Mobil Super Multigrado 20W-50 is designed to provide a high level of performance and protection under most operating conditions.

Features and Benefits

Engine protection during start up

Extended protection against engine wear and deposits formation

Helps combat sludge

Mobil Super Multigrado 20W-50 is meticulously engineered for today's tougher engine specifications. It provides very good engine protection and helps promote long engine life.

Applications

Mobil Super Multigrado 20W-50 has been formulated to be suitable for use in nearly all vehicles. ExxonMobil particularly recommend Mobil Super Multigrado 20W-50 for daily driving under normal conditions:

- Nearly all gasoline engine technologies
- Passenger cars, SUV's, light trucks and vans
- Normal Operating Conditions
- Suitable for use under a wide range of temperature conditions

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product meets or exceeds the requirements of:
API SP
API SN PLUS
API SN
API SM

This product meets or exceeds the requirements of:

API SL

API SJ

Properties and Specifications

Property	
Grade	SAE 20W-50
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	4.9
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	167
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	19.5
Flash Point, °C, ASTM D92	252
Ash, Sulfated, wt%, ASTM D874	0.7
Density @ 15 C, g/ml, ASTM D4052	0.874
Pour Point, °C, ASTM D97	-27

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

06-2021

Terpel-Comercial Ecuador Compañía Limitada

Dirección : Av. Joaquín Orrantía, Edificio Solaris, Piso 12, Oficinas (801-812), Guayaquil – Ecuador

Teléfono: +593 42634060

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved