



Mobil™ X4 50

Mobil Commercial Vehicle Lube , Egypt

High performance monograde diesel engine oil

Product Description

Mobil™ X4 50 is a high performance monograde diesel engine oil specifically engineered for performance in intercooled, turbo-charged engines operating under severe on and off-highway conditions. Mobil X4 50 is used in a wide range of applications where a monograde lubricant is recommended: Trucking, mining, quarrying, construction, and agricultural businesses use this product successfully.

Features and Benefits

The benefits of Mobil X4 50 monograde include:

Features	Advantages and Potential Benefits
Excellent protection against oil thickening, high temperature deposits, sludge build-up, oil degradation and corrosion	<p>Helps to prolong engine life</p> <p>Helps to protect against ring sticking</p> <p>Helps to control wear</p>

Applications

Recommended by ExxonMobil for use in:

- Naturally aspirated and turbo-charged diesel powered equipment
- On-highway light and heavy duty trucking
- Off-highway industries including: construction, mining, quarrying, and agriculture

Properties and Specifications

Property	
Grade	SAE 50
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	20.1
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	229
Viscosity Index, ASTM D2270	101
Pour Point, °C, ASTM D97	-15
Flash Point, °C, ASTM D92	253
Density @ 15 C, g/ml, ASTM D1298	0.905

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims>

[/psims.aspx](#)

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

01-2022

ExxonMobil Egypt (S.A.E.)

1097 Cornish El-Neil, Garden City, Cairo, Egypt

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.global.mobil.com/en/contact-us>

+ 20 2 795 4850/60

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil  

© Copyright 2003-2022 Exxon Mobil Corporation. All Rights Reserved