



Mobil Gargoyle Arctic 68 NH

Mobil Industrial , Egypt

Refrigeration Oil for Ammonia (R-717) application

Product Description

Mobil Gargoyle Arctic 68 NH is a high performance refrigeration oil designed specifically for the lubrication of refrigeration reciprocating and screw compressor: ammonia (NH₃, R-717). It is formulated with high quality mineral paraffinic technology providing excellent low temperature performance, low volatility and thermal stability.

Its very low miscibility with ammonia limits oil thinning and minimizes oil carry-over. Low vapour pressure reduces oil consumption and need for top-ups while prevents fractionation (viscosity increase).

Viscosity control over a wide temperature range to obtain the lowest fluidity required in the evaporator and the highest viscosity for enhanced equipment protection of the compressor.

Features and Benefits

- Low volatility, helps reducing oil consumption (fewer oil top-ups), limiting oil thinning from fractionation
- Low Brookfield viscosity contributes to good oil flow at low temperatures and good oil return from evaporator
- Surface protection for increased equipment life, reduced repair costs
- High Viscosity Index for good compressor lubrication across wide operating temperatures
- Refrigerant compatibility contributes to oil separator efficiency (very low miscibility with NH₃)

Applications

Application considerations: Mobil Gargoyle Arctic 68 NH is recommended for refrigeration systems for cylinder and bearing lubrication in conventional reciprocating and screw refrigeration compressors where ammonia refrigerant is used.

This includes:

- Large industrial reciprocating and screw refrigeration compressors used in the food industry for food preparation and freezing
- Industrial applications such as food freezing and cold storage plants
- Marine refrigeration applications

Typical Properties

| Viscosity | | |
|------------------------------------|------------|------|
| cSt @ 40° C | ASTM D445 | 68.6 |
| cSt @ 100° C | ASTM D445 | 9.32 |
| Viscosity Index | ASTM D2270 | 113 |
| Pour Point (°C) | ASTM D5950 | -39 |
| Flash Point (°C) | ASTM D92 | 248 |
| Density @ 15°C | ASTM D4052 | 0.86 |
| Brookfield Viscosity at -20°C (cP) | ASTM D2983 | 6020 |

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

06-2023

ExxonMobil Egypt (S.A.E.)

1097 Cornish El-Nil, Garden City, Cairo, Egypt

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.global.mobil.com/en/contact-us>


+ 20 2 795 4850/60

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All properties may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved