



Mobil Super™ Semi-Synthetic 10W-40

Mobil Passenger Vehicle Lube , Egypt

Premium Semi-Synthetic Passenger Vehicle Engine Oil

Product Description

An extra high performance semi-synthetic motor oil, providing engine protection up to 8000 KM.

Features and Benefits

Mobil Super™ Semi-Synthetic 10W-40 provides engine protection and helps promote long engine life:

- Effective sludge prevention
- Good engine cleanliness
- Robust wear protection
- High temperature protection

Applications

Mobil Super™ Semi-Synthetic 10W-40 is formulated for city driving conditions of gasoline and diesel vehicles over a wide range of temperatures. High wear prot and engine cleanliness performance helps to prolong enigne life.

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle

Specifications and Approvals

This product meets or exceeds the requirements of:
API SM
API SN

Properties and Specifications

Property	
Grade	SAE 10W-40
Cold-Cranking Simulator, Apparent Viscosity @ -25 C, mPa.s, ASTM D5293	5420
Ash, Sulfated, mass%, ASTM D874	0.9
Flash Point, Cleveland Open Cup, °C, ASTM D92	234
Pour Point, °C, ASTM D97	-33
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	94.6
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	14.2
Total Base Number, mgKOH/g, ASTM D2896	9.9

Property	
Viscosity Index, ASTM D2270	155

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2022
ExxonMobil Egypt (S.A.E.)
1097 Cornish El-Nil, Garden City, Cairo, Egypt

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.global.mobil.com/en/contact-us>
+ 20 2 795 4850/60
<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product perfor are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All pr may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is inten override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entit

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved