



**Mobil 1™ FS X2 5W-50**  
Mobil Passenger Vehicle Lube , Egypt  
Advanced Full Synthetic Motor Oil

**Product Description**

Mobil 1™ FS x2 5W-50 advanced performance synthetic engine oil is a select member of Mobil 1™, the world's leading synthetic engine oil brand delivering our ul performance and protection.

Mobil 1 FS x2 5W-50 is engineered to deliver excellent all-round protection for engines operating in tough conditions. It is suitable for high performance and motc applications requiring high viscosity engine oils, and addresses the specific demands of older vehicles even above 100,000 km.

Racing or normal driving, Mobil 1 FS x2 5W-50 helps to provide heavy-duty engine performance and protection for an outstanding driving experience. Mobil 1 your engine running like new!

**Features and Benefits**

Mobil 1 FS x2 5W-50 combines a proprietary blend of high performance synthetic base stocks fortified with a precisely balanced component system provi reinforced protective oil film at high temperature while still ensuring superb oil flow properties at lower temperatures. Its full SAPS additive system contributes as exceptional cleaning power, engine wear protection and lubrication up to 20,000 km maximum oil drain interval.

- Excellent protection for your engine by helping to prevent the buildup of harmful deposits.
- Enhanced cleaning technology for cars with higher mileage (100 000km +).
- Improved protection against variable fuel quality\*.
- Low temperature viscosity grade (SAE 5W) to help protect your engine during cold start-up.
- High temperature viscosity grade (SAE 50) to help build a strong lubricating oil film to protect against wear, and to help reduce oil consumption or leaks in high-r engines.
- Helps prevent Low Speed Pre-Ignition (LSPI) occurrences and timing chain wear in gasoline direct injection turbocharged engines (GTDI).

\* Performance compared in industry standard tests, which use fuels designed to promote sludge formation.

**Applications**

Mobil 1 FS x2 5W-50 is suitable for the latest generation high powered vehicles with gasoline and Diesel engines (without Particulate Filter), turbo-charged or na aspirated, as well for the older gasoline engines calling fo high viscosity engine oils meeting prior API standards.

- It is well suited for motorsport applications and extreme driving conditions (high temperatures and loads, car towing...).
- Mobil 1 FS x2 5W-50 helps also provide the extra protection that older vehicles and vehicles with higher mileage (> 100 000 km) can demand.

Always consult your owner's manual to check the recommended viscosity grade, specifications and drain interval for your particular vehicle.

**Specifications and Approvals**

<b>This product has the following approvals:</b>
MB-Approval 229.3
Porsche A40

**This product is recommended for use in applications requiring:**

API CF

FIAT 9.55535-M2

**This product meets or exceeds the requirements of:**

API SJ

API SL

API SM

API SN

API SN PLUS

API SP

ACEA A3/B3

ACEA A3/B4

LEXUS LFA Service Fill

**Properties and Specifications**

Property	
Grade	SAE 5W-50
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	18.6
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	112
Viscosity Index, ASTM D2270	185
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	4.3
Pour Point, °C, ASTM D97	-39
Flash Point, Cleveland Open Cup, °C, ASTM D92	225
Total Base Number, mgKOH/g, ASTM D2896	13
Density @ 15.6 C, g/ml, ASTM D4052	0.841

**Health and safety**

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

ExxonMobil Egypt (S.A.E.)

1097 Cornish El-Nil, Garden City, Cairo, Egypt

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.global.mobil.com/en/contact-us>

+ 20 2 795 4850/60

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved