



## Mobil Super™ Synthetic Technology x1™ 10W-40

Mobil Passenger Vehicle Lube , Egypt

Premium Synthetic Blend

### Product Description

Semi-synthetic motor oil engineered to provide excellent performance under an extensive range of conditions. Formulated to give you the confidence of protection beyond that of conventional oils up to 8000 km, we particularly recommend this product if you occasionally experience demanding driving conditions where it can combat the damage caused by high engine stress. Recommended for Gasoline engines.

### Features and Benefits

Mobil Super™ Synthetic Technology x1™ 10W-40 provides engine protection and helps promote long engine life:

- Effective sludge prevention
- Good engine cleanliness
- Robust wear protection
- High temperature protection

### Applications

Mobil Super™ Synthetic Technology x1™ 10W-40 is formulated for city driving conditions of gasoline and diesel vehicles over a wide range of temperatures. High protection and engine cleanliness performance helps to prolong engine life.

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle

### Specifications and Approvals

#### This product is recommended for use in applications requiring:

API CF

MB 229.1

#### This product meets or exceeds the requirements of:

API SJ

API SL

API SM

API SN

API SN PLUS

### Properties and Specifications

Property	
----------	--

Property	
Grade	SAE 10W-40
Cold-Cranking Simulator, Apparent Viscosity @ -25 C, mPa.s, ASTM D5293	5420
Viscosity Index, ASTM D2270	155
Total Base Number, mgKOH/g, ASTM D2896	9.9
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	14.2
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	94.6
Flash Point, Cleveland Open Cup, °C, ASTM D92	234
Pour Point, °C, ASTM D97	-33

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

07-2023

ExxonMobil Egypt (S.A.E.)

1097 Cornish El-Nil, Garden City, Cairo, Egypt

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.global.mobil.com/en/contact-us>


+ 20 2 795 4850/60

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All properties may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved