



## Mobil™ Coolant Ready Mixed 50%

Mobil Passenger Vehicle Lube , Egypt

High Performance Coolant

### Product Description

Mobil™ Coolant Ready Mixed 50% is a high performance coolant designed to provide efficient protection in all seasons. It is a ready to use product that has been premixed with antifreeze and water.

Mobil™ Coolant Ready Mixed 50% contains Glysantin® G48® engine coolant concentrate that is nitrite-free, free of amines and phosphates, and contains ethylene glycol.

Mobil™ Coolant Ready Mixed 50% acts as both antifreeze and coolant, and imparts very good anticorrosion protection to all metal parts found in the cooling systems of internal combustion engines.

### Features and Benefits

Mobil™ Coolant Ready Mixed 50% provides following benefits:

- Outstanding protection against frost and overheating in all modern engines, but especially highly loaded aluminum engines.
- Effective protection against corrosion and deposits in the cooling system vital parts.
- Easy circulation through the engine block and cylinder head channels, the radiator, and the heater enabling cooler operation and protection of the engine.

### Applications

Mobil™ Coolant Ready Mixed 50% contains Glysantin® G48® from BASF approved by many OEMs, of which:

- Audi/Seat/Skoda/VW (vehicles built up until 1996) TL 774-C
- BMW N.600 69.0
- MAN 324-NF
- Maybach Specification 325.0
- Mercedes-Benz Specification 325.0
- MINI (BMW) BMW N 600 69.0
- MTU MTL 5048
- Opel/Vauxhall (vehicles built up until 2000)B 040 0240
- Saab 690 1599
- Smart Specification 325.0
- Volvo Cars 1286083 Issue 002

### Properties and Specifications

Property	
Density @ 15 C, g/ml, ASTM D4052	1.081
Color, Visual	Greenish Blue

Property	
pH, ASTM D1287	8
Appearance, Visual	Clear

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

ExxonMobil Egypt (S.A.E.)

1097 Cornish El-Nil, Garden City, Cairo, Egypt

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.global.mobil.com/en/contact-us>

+ 20 2 795 4850/60

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved