



Mobil Almo 500 Series

Mobil Industrial , Spain

Pneumatic Rock Drill and Tool Lubricants

Product Description

Mobil Almo 500 Series lubricants are premium quality high performance products primarily intended for the lubrication of pneumatically operated rock c underground and surface mining operations. The Mobil Almo Series oils are formulated from high quality base stocks and additives, which provide excellent ch stability and good protection against wear and corrosion. They offer an optimum balance of adhesiveness, yet are emulsifiable enough to pick up moisture carried air stream reducing the negative effects of water on wear and corrosion. They do not form gummy deposits that could cause sluggish valve action. Even in the pre of water, the Mobil Almo 500 Series oils have good preferential metal-wetting properties that maintain continuous oil films. These properties in combination with h characteristics help provide excellent lubrication resulting in long equipment life.

Mobil Almo 500 Series possess high viscosity indexes and low pour points to ensure good lubrication at the low temperatures resulting from air expansion and against icing stoppages while providing adequate films on drill parts that may operate at high temperatures. Oil fog generation levels are extremely low.

Features and Benefits

The Mobil Almo 500 Series oils provide an optimum performance balance which assures long equipment life and minimal maintenance costs. Their excellen protection characteristics and ability to provide adequate lubrication in the presence of water not only reduces wear but protects against rust and corrosion. Thei chemical stability prevents sludge and deposit formation reducing the need for frequent maintenance.

Features	Advantages and Potential Benefits
Effective Chemical Stability	Reduce sludge and deposit formation Improves valve operation
Desired Emulsifiable Properties	Effective lubrication in presence of water
High Viscosity Index	Provides good lubrication at both high and low temperatures
Excellent Load Carrying Ability and Anti-Wear Protection	Reduces component wear Prolongs equipment life Reduces maintenance costs
Very Good Adhesive Characteristics	Protects metal surfaces from corrosion Provides good lubricant films under all conditions
Rust and Corrosion	Longer tool life Increased tool performance

Applications

Mobil Almo 500 Series oils are recommended for use in all pneumatically operated rock drills in both underground and surface mining as well as in contractor and industrial applications. They are suitable for percussive- and rotary- type tools. The viscosity grades allow selection for year-round use where seasonal ar temperature variations are extreme.

- Pneumatically operated rock drills in underground and surface mining operations
- Pneumatically operated drills and jack hammers in highway construction and building operations
- Rock drills in quarry operations
- Percussion and rotary air-operated tools in industrial applications

Properties and Specifications

Property	MOBIL 524	ALMO	MOBIL 525	ALMO	MOBIL 527	ALMO	MOBIL 529	ALMO	MOBIL 530	ALMO	MOBIL 532	ALMO
Grade	ISO 32		ISO 46						ISO 220		ISO 320	
Density @ 15.6 C, kg/l, ASTM D4052	0.88		0.883		0.899		0.893		0.898		0.902	
Flash Point, Cleveland Open Cup, °C, ASTM D92	170		188		220		220		220		232	
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	5.5		7.3		11.5		16.5		19.7		24.9	
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	32		46		100		172		220		320	
Pour Point, °C, ASTM D97	-51		-30		-27		-24		-24		-21	
Viscosity Index, ASTM D2270	108		105		100		102		100		99	

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>  
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

06-2023  
ExxonMobil Lubricants and Specialties Europe division of ExxonMobil Petroleum & Chemical b.v.b.a.  
Polderdijkweg  
B-2030 Antwerpen, Belgium  
<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)  
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil

Esso

XT

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved