



Mobil Super 15W-50

Mobil Passenger Vehicle Lube , Ethiopia

Premium Multigrade Passenger Vehicle Engine Oil

Product Description

An extra high performance motor oil for all types of vehicles, providing ultimate engine protection up to 5000 KM. The heat activated anti-wear molecule protects your engine against wear and corrosion, ensuring long engine life.

Features and Benefits

Mobil Super 15W-50 provides engine protection and helps promote long engine life:

- Extended protection against engine wear and deposits formation
- Engine protection during start up
- Helps combat sludge

Applications

Mobil Super 15W-50 has been formulated to be suitable for use in vehicles requiring an API SL, API SN, API SM and API SJ claims . ExxonMobil particularly recommend Mobil Super 15W-50 for daily driving:

- Under normal Operating Conditions
- Suitable for use under a wide range of temperature conditions

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

According to ExxonMobil, this product is of the following quality level:

API CF

MOBIL SUPER 15W-50 meets or exceeds the requirements of:

API SJ

API SL

API SM

API SN

Properties and Specifications

Property	
----------	--

Property	
Grade	SAE 15W-50
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	17.95
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	139.5
Viscosity Index, ASTM D2270	144
Ash, Sulfated, mass%, ASTM D874	0.91
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	4.68
Pour Point, °C, ASTM D97	-30
Flash Point, Cleveland Open Cup, °C, ASTM D92	226
Density @ 15 C, g/ml, ASTM D4052	0.8768

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

03-2021

ExxonMobil Egypt (S.A.E.)

1097 Cornish El-Nil, Garden City, Cairo, Egypt

+ 20 2 795 4850/60

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil  

© Copyright 2003-2022 Exxon Mobil Corporation. All Rights Reserved