



MOBILCUT 320-NEW

Mobil Industrial , Finland  
Aqueous Metal Working Fluid

Product Description

Mobilcut is the trademark for Mobil Industrial lubricants line of high performance water miscible metal removal fluids. Formulated with leading edge base oils, additives and emulsifiers, the Mobilcut series of non-chlorinated products provides dependable performance in a wide array of metal removal processes. The products are designed to work in a variety of hard and soft water qualities and offer low foam potential and long-term corrosion protection for machine and component maintenance and inherently stable, Mobilcut products are designed for the modern machine shop where long service life, excellent machining performance, health and environmental concerns are important factors for increased productivity. These products are supplied in concentrated form and require mixing with water at the point of use. All Mobilcut products are free of formaldehyde release agents (FAD).

Mobilcut 320-New is boron free high quality synthetic water miscible metalworking fluid designed for general grinding operations with steel and cast iron where excellent quality surface finish, outstanding cooling and low foaming potential are the primary requirements.

Features and Benefits

The Mobilcut series are designed to help increase the productivity of modern machine shops by providing high performance features

Features	Advantages and Potential Benefits
Form stable emulsions and solutions	Ease of use and maintenance
Long term inherent stability	Increases batch life and reduces unpleasant odors
Low foaming potential	Improved performance even in high pressure systems
Resists formation of sticky residues	Improves machine cleanliness
High degree of corrosion protection	Reduces machine maintenance and rework of materials
Good separability from fines	Improves filterability and surface finish
Wide Range of applicability	Potential to consolidate products and reduce inventories
Compatible with high performance Mobil Vactra Oil No slideway lubricants	Easy separation and removal of tramp oil
Neutral Odor	Enhances the workplace environment

Applications

Mobilcut 320-New: Synthetic (mineral oil-free) grinding fluid, primarily recommended for grinding of steels and cast iron. Not suitable for Tungsten Carbide. Fluid is a chemical solution. Water hardness range is from 0 to 20 °dH with a possibility to go up to 40°dH in use. Its refractometer factor is 1.4.

Recommended concentrations for typical operations:

- Low alloy steels grinding: 5-8%
- Carbon alloy steels grinding: 8-10%
- Cylindrical & Surface grinding: 5-8%

Properties and Specifications

Property	
----------	--



Property	
Appearance, AA.Lab.101	Liquid, Yellow
Appearance, 5.0% in 20 deg dH Water, AA.Lab.101	Clear and Colorless
Kinematic Viscosity 20 C, mm2/s, DIN EN ISO 3104	70
Density 15 C, kg/m3, DIN EN ISO12185	1085
pH-Value 5.0% in 20 deg dH Water, DIN 51369	9.5

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>  
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2020  
ExxonMobil Finland Oy Ab  
Satamatie 10  
21100 Naantali - FINLAND

+358 (0) 10 40 8500  
<http://www.mobil.fi>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All properties may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)  
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil

Esso

ExxonMobil

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved