



Mobil Super™ 3000 Formula RN 5W-30

Mobil Passenger Vehicle Lube , Finland

Mobil Passenger Vehicle Lube

Product Description

Mobil Super™ 3000 Formula RN 5W-30 is a synthetic high-performance low ash engine oil developed to meet RN17, Renault's latest specification for modern gasoline and diesel vehicles. It is particularly suited to help prolong the life and maintain the efficiency of particulate filters and catalytic converters found on diesel and gasoline vehicles put into circulation since mid 2018 to respond to European latest emissions regulation.

Features and Benefits

- Suitable for use in most Renault gasoline and diesel passenger cars and light commercial vehicles.
- Helps to maintain the efficiency of the exhaust emission reduction systems in both diesel and gasoline vehicles.
- Contributes to keep engine clean from deposits for optimal efficiency and long life.
- Permits extended operation at elevated temperatures without detrimental oxidative oil thickening or breakdown.
- Provides excellent fluidity at low temperatures allowing easy winter starting and rapid oil circulation and protection throughout the engine.

Specifications and Approvals

This product has the following approvals:
RENAULT RN17

This product meets or exceeds the requirements of:
ACEA C3

Properties and Specifications

Property	
Grade	SAE 5W-30
Appearance, AMS 1738	Amber Liquid
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	64.4
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	12.3
Pour Point, °C, ASTM D97	-42
Flash Point, Pensky-Martens Closed Cup, °C, ASTM D93	212

Property	
Ash, Sulfated, mass%, ASTM D874	0.8
Phosphorus, mass%, ASTM D4951	0.08
Sulfur, mass%, ASTM D2622	0.2
Density @ 15 C, g/ml, ASTM D1298	0.852

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2020

ExxonMobil Finland Oy Ab
Satamatie 10
21100 Naantali - FINLAND

+358 (0) 10 40 8500

<http://www.mobil.fi>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil  

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved