



Mobilgrease CM Series

Mobil Grease , Fiji

Grease

Product Description

Mobilgrease CM Series products are a family of extra high performance extreme-pressure greases. Mobilgrease CM-P and CM-S are NLGI Grade 2, while Mobil CM-W and CM-L are NLGI Grade 1. All four products are manufactured with a proprietary high-temperature, lithium complex thickener system. They exhibit ex resistance to softening under severe working, and provide good adhesion and cohesion. An extreme-pressure additive provides exceptional protection against while additional additives enhance resistance to high-temperature oxidation and protection against rust. In addition, Mobilgrease CM-P and Mobilgrease CM-L c 3% molybdenum sulphide for additional wear protection. Other formulation features provide low-temperature dispensing, very good resistance to water wash, an service in bearings operating at high temperatures. These heavy-duty, severe-service greases have outstanding structural and chemical stability. Mobilgrease CM products won't corrode steel or copper-bearing alloys and are compatible with conventional seal materials.

Mobilgrease CM greases are recommended by ExxonMobil for use in for construction and mining sector applications. Mobilgrease CM-P is recommended by Exxon for use in for highly loaded plain and antifriction bearings and other applications where the three percent molybdenum disulphide and high-temperature thickener s will provide extraordinary performance. Mobilgrease CM-S is recommended by ExxonMobil for use in plain and antifriction bearings in contractor and mining v working under severe operating and weather conditions. The recommended application temperature range for Mobilgrease CM-P and CM-S is -20° C to +1 Mobilgrease CM-L and CM-W are winter-grade products and are recommended for cold-temperature service. The recommended application temperature rar Mobilgrease CM-L and CM-W is -30° C to +145° C

Features and Benefits

Mobilgrease CM Series greases are designed specifically to meet the needs of customers with heavily loaded equipment that require high EP/antiwear perfor which remain in place even in tough conditions of water wash, high sliding and high temperature. These greases are targeted especially for the severe constructi mining sector and offer the following features and potential benefits:

Mobilgrease CM Series greases are leading members of the Mobilgrease brand of products, which has gained a world-wide reputation for innovation and perfor excellence. Mobilgrease CM Series grease products are designed by our formulation technologists and backed by our world-wide technical support staff.

| Features | Advantages and Potential Benefits |
|---|---|
| Excellent resistance to water, including spray | Maintains excellent lubrication properties and protects equipment in conditions of water contamination |
| Very good EP and anti-wear protection | Lower maintenance costs and less unanticipated downtime |
| Better stay-put properties at high temperatures | Excellent performance in high shear, high load applications, especially where grease re-supply is limited |
| Resists rust and corrosion | Protects equipment in presence of water for reduced maintenance and longer equipment life |
| Good pumpability at low temperatures | Excellent low temperature properties including start-up in remote locations |

Applications

Recommended by ExxonMobil for use in:

- Heavily loaded applications or environments highly contaminated with water, especially in the contractor / mining sector. Specific examples of such applic include:
- Heavy-duty trucks especially, hinge and bucket pins
- Mining and construction equipment

Specifications and Approvals

| | |
|--|------|
| This product meets or exceeds the requirements of: | CM-P |
| DIN 51825: 2004-06 KPF2N-20L | X |

Properties and Specifications

| Property | CM-L | CM-P | CM-S | CM-W |
|--|-----------------|-----------------|-----------------|--------------|
| Grade | NLGI 1 | NLGI 2 | NLGI 2 | NLGI 1 |
| Thickener Type | Lithium Complex | Lithium Complex | Lithium Complex | Lithium Comp |
| Color, Visual | Gray-Black | Gray-Black | Orange | Orange |
| Copper Strip Corrosion, 24 h, 100 C, Rating, ASTM D4048 | 1A | 1A | 1A | 1A |
| Corrosion Preventive Properties, Rating, ASTM D1743 | Pass | Pass | Pass | Pass |
| Dropping Point, °C, ASTM D2265 | 260 | 260 | 260 | 260 |
| Four-Ball Extreme Pressure Test, Weld Point, kgf, ASTM D2596 | 400 | 400 | 250 | 250 |
| Four-Ball Wear Test, Scar Diameter, mm, ASTM D2266 | 0.5 | 0.5 | 0.5 | 0.5 |
| Penetration, 60X, 0.1 mm, ASTM D217 | 325 | 280 | 280 | 325 |
| Roll Stability, Penetration Consistency Change, 0.1 mm, ASTM D1831 | -15 | -3 | -4 | -15 |
| Viscosity @ 100 C, Base Oil, mm2/s, ASTM D445 | 14.5 | 23.9 | 23.9 | 14.5 |
| Viscosity @ 40 C, Base Oil, mm2/s, ASTM D445 | 150 | 320 | 320 | 150 |
| Viscosity Index, ASTM D2270 | 94 | 95 | 95 | 94 |
| Water Washout, Loss @ 79 C, wt%, ASTM D1264 | 12 | 6 | 6 | 12 |

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

06-2023

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved