



Mobil Super™ 1000 10W-30

Mobil Passenger Vehicle Lube , Fiji

Premium Multigrade Passenger Vehicle Engine Oils

Product Description

The Mobil Super 1000 10W-30 is a range of quality premium mineral motor oils designed to provide a high level of performance and protection under most operating conditions.

Features and Benefits

Mobil Super 1000 10W-30 is meticulously engineered for today's tougher engine specifications. It provides very good engine protection and extends engine life.

- Designed to provide very good wear protection
- Helps to maintain

engine cleanliness

Applications

Mobil Super 1000 10W-30 is suitable for use in both gasoline and diesel powered vehicles. Mobil Super 1000 10W-30 is ideally suited for less stressful driving conditions such as highway driving and lower consistent speed conditions.

Specifications and Approvals

This product meets or exceeds the requirements of:	10W-30
API SN	X
API SM	X
API SL	X

This product is recommended for use in applications requiring:	10W-30
API CF	X

Typical Properties

Mobil Super 1000	
SAE Grade	10W-30
Viscosity, ASTM D 445	
cSt @ 40°C	67.1
cSt @ 100°C	10.3

Mobil Super 1000	
Viscosity Index, ASTM D 2270	139
Sulfated Ash, wt%, ASTM D 874	0.9
HTHS Viscosity, mPa·s @ 150°C, ASTM D4683	3.0
Pour Point, °C, ASTM D 97	-31
Flash Point, °C, ASTM D 92	230
Density @ 15 °C, kg/l, ASTM D4052	0.870

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

06-2022

ExxonMobil

Exxon Mobil  

© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved