



Mobil 1™ 5W-30

Mobil Passenger Vehicle Lube , Fiji

Advanced Full Synthetic Engine Oil

Product Description

Mobil 1™ Triple Action Power advanced full synthetic engine oil delivers outstanding engine Performance, Protection, and Cleanliness.

Features and Benefits

Why these matter for your engine:

- **PERFORMANCE:** Reduces the stress of daily wear and harsh conditions for longer engine life.
- **PROTECTION:** Guards against extreme temperatures to prevent breakdowns.
- **CLEANLINESS:** Prevents buildup of contaminants and sludge for a cleaner engine.

Mobil 1™ Triple Action Power is feature packed to:

- **PERFORM:** Keeps your engine running like new.
- **PROTECT:** 10X* better protection for high temperatures.
- **CLEAN:** Fights sludge with active cleaning agents.

*Based on Sequence IIIH, against API SP specification

Applications

Mobil 1™ Triple Action Power is suitable for use in petrol, diesel, and hybrid vehicles.

Always check your owner's manual for the recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product has the following approvals:
HONDA/ACURA HTO-06

This product is recommended for use in applications requiring:
Ford WSS-M2C929-A
Ford WSS-M2C946-A
Ford WSS-M2C946-B1
FIAT 9.55535-CR1

This product meets or exceeds the requirements of:

FORD WSS-M2C961-A1

Chrysler MS-6395

CHRYSLER MS-13340

API SP Resource Conserving

API SP

API SN PLUS

API SN

API SM

ILSAC GF-6A

ACEA A5/B5

ACEA C2

Properties and Specifications

Property	
Grade	SAE 5W-30
Total Base Number, mgKOH/g, ASTM D2896	9.2
Ash, Sulfated, mass%, ASTM D874	0.76
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	61
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	10.3
Mini-Rotary Viscometer, Apparent Viscosity, -35 C, mPa.s, ASTM D4684	13700
Pour Point, °C, ASTM D97	-39
Flash Point, Cleveland Open Cup, °C, ASTM D92	235
Density @ 15.6 C, g/ml, ASTM D4052	0.852
Viscosity Index, ASTM D2270	157

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

07-2023

ExxonMobil



© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved