



Mobil Delvac™ Light Commercial Vehicle E 10W-40

Mobil Commercial Vehicle Lube , France

Light Commercial Vehicle Engine Oil

Product Description

Mobil Delvac™ Light Commercial Vehicle E 10W-40 is a semi-synthetic engine oil that provides long engine life and excellent engine protection against sludge & wear.

Mobil Delvac™ Light Commercial Vehicle E 10W-40 provides excellent lubrication of diesel and gasoline engines operating in severe driving conditions typically encountered in city operations. This product is recommended by ExxonMobil for European engines for use in a wide range of traditional light-duty commercial vehicles.

Features and Benefits

Mobil Delvac™ Light Commercial Vehicle E 10W-40 is formulated from high performance base oils and a superior balanced additive system to provide optimum engine performance in recent diesel and gasoline engines as well as older models. Key benefits include:

Features	Advantages and Potential Benefits
Increased thermal and oxidation stability	Help to reduced sludge build-up, deposits, and long oil and engine life
Enhanced wear protection	Helps towards long component and engine life
Advanced piston deposit control	Helps to keep engines clean with reduced maintenance costs and long engine life
Advanced soot handling to control viscosity increase, sludge build up, and filter pressure	Helps to enhance engine protection for long engine life
Enhanced low temperature pumpability	Fast start up with reduced wear operating in low temperature climates

Applications

ExxonMobil recommends Mobil Delvac™ Light Commercial Vehicle E 10W-40 for demanding driving conditions:

- Older engine technologies
- Gasoline and Diesel without Diesel Particulate Filters (DPF)
- Light trucks and vans
- Normal to occasionally severe operating conditions

Specifications and Approvals

This product has the following approvals:
VW 501 01
VW 505 00

This product is recommended for use in applications requiring:

MB-Approval 229.1

This product meets or exceeds the requirements of:

API SN PLUS

ACEA A3/B3

Properties and Specifications

Property	
Grade	SAE 10W-40
Flash Point, Cleveland Open Cup, °C, ASTM D92	234
Ash, Sulfated, mass%, ASTM D874	0.9
Cold-Cranking Simulator, Apparent Viscosity @ -25 C, mPa.s, ASTM D5293	5400
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	95
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	14.2
Density @ 15.6 C, g/ml, ASTM D4052	0.87
Total Base Number, mgKOH/g, ASTM D2896	9.9
Viscosity Index, ASTM D2270	155
Pour Point, °C, ASTM D97	-33

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

07-2020

Esso Société Anonyme Française

20 rue Paul Héroult
92000 Nanterre, France

Société Anonyme au capital de 98 337 521,70 euros

RCS Nanterre 542 010 053

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.mobil.fr/fr-fr/contact-us>

Tel. +33 (0)1 49 67 90 00

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil

Esso

XTO
ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All
Rights Reserved