



Mobil Pyrotec™ HFD 46

Mobil Industrial , France

Fire-Resistant Hydraulic Fluid

Product Description

Mobil Pyrotec HFD 46 is a high performance fire resistant hydraulic fluid. It is designed for use in electro-hydraulic governor control systems of steam turbines, including systems using fine tolerance servo valves. It is also recommended as a fire resistant lubricant in, for example, steam and gas turbines as well as fire resistant hydraulic systems. Mobil Pyrotec HFD 46 is FM approved as a fire resistant industrial fluid.

Mobil Pyrotec HFD 46 is formulated to provide good oxidation stability. Physical properties such as foaming, air release and demulsibility are controlled to meet the limits specified by turbine manufacturers.

Mobil Pyrotec HFD 46 has been evaluated in stringent tests for fire resistance. It will burn if the bulk fluid temperature reaches 368°C and is exposed to an open flame. However, in the spray ignition hot manifold ignition test there is no flashing or burning at 704°C.

Features and Benefits

Mobil Pyrotec HFD 46 has the following benefits:

- Inherent resistance to fire hazards
- Long component life due to excellent anti-wear properties
- Long fluid life due to high oxidation resistance
- FM approved

Applications

Mobil Pyrotec HFD 46 is recommended for use in:

- Electro-hydraulic governor control systems of steam turbines, especially where a high performance fluid is required
- Hydraulic and oil circulation systems operating in conditions subject to fire hazards

Mobil Pyrotec HFD 46 is unsuitable for:

- Hydraulic systems subjected to low temperatures. The normal operating temperature should normally be up to 65°C to minimize thermal degradation. However, it is possible to operate with fluid temperatures up to a maximum of 150°C.
- Use with Neoprene, nitrile and silicone rubber materials. Mobil Pyrotec HFD 46 is compatible with seal and hose materials such as butyl rubber and Viton.
- Use with petroleum oils, conventional soluble emulsions, water in oil emulsions or water glycol fluids. ExxonMobil will be pleased to give advice on flushing procedures.
- Use on most paints (other than two part epoxy paints), enamels and varnishes. Because of the solvent properties of Mobil Pyrotec HFD 46, it is necessary, therefore, to consider treating all internal surfaces likely to come into contact with it.

Specifications and Approvals

This product has the following approvals:

FM Global Approvals Class 6930

Properties and Specifications

Property	
Grade	ISO 46
Appearance, AMS 1738	Colorless
Flash Point, Cleveland Open Cup, °C, ISO 2592	270
Kinematic Viscosity @ 40C, mm ² /s, ISO 3104	44

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

02-2022

Esso Société Anonyme Française

20 rue Paul Héroult
92000 Nanterre, France

Société Anonyme au capital de 98 337 521,70 euros

RCS Nanterre 542 010 053

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.mobil.fr/fr-fr/contact-us>

Tel. +33 (0)1 49 67 90 00

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil



© Copyright 2003-2022 Exxon Mobil Corporation. All Rights Reserved