



Mobil Super™ 3000 X1 5W-40

Mobil Passenger Vehicle Lube , France

Premium Full Synthetic Passenger Vehicle Motor Oil

Product Description

Mobil Super™ 3000 x1 5W-40 is a fully synthetic engine oil that provides long engine life for many types and ages of vehicles with enhanced protection over a wide temperature range.

Features and Benefits

Mobil Super 3000 products are industry proven so you can trust you will get the protection you want from your vehicle. Mobil Super 3000 x1 5W-40 provides:

- Enhanced high temperature protection
- Enhanced cold start-up protection
- Enhanced engine cleanliness and sludge prevention
- Enhanced wear protection

Applications

Mobil Super 3000 products are formulated to give you confidence of protection beyond that of conventional or semi-synthetic oils. ExxonMobil recommends Super 3000 x1 5W-40 if you regularly experience demanding conditions where it can help combat the damage caused by frequent high engine stress:

- Passenger cars, SUV's, light trucks and vans
- Gasoline and Diesel engines, without particulate filters (DPF)
- High performance engines with turbo-chargers and direct injection
- Highway cruising and stop and go city driving
- Normal to frequently severe operating conditions

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product has the following approvals:
Porsche A40
PSA B71 2296
RENAULT RN0700
RENAULT RN0710
VW 502 00
VW 505 00
MB-Approval 229.3

This product has the following approvals:

AVTOVAZ (LADA cars)

This product is recommended for use in applications requiring:

API CF

FIAT 9.55535-G2

This product meets or exceeds the requirements of:

ACEA A3/B4

API SL

API SM

API SN

Fiat 9.55535-M2

AAE (STO 003) Group B6

Properties and Specifications

Property	
Grade	SAE 5W-40
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	13.2
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	79
Density @ 15.6 C, g/ml, ASTM D4052	0.847
Pour Point, °C, ASTM D97	-39
Flash Point, Cleveland Open Cup, °C, ASTM D92	236

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

03-2024

Esso Société Anonyme Française

20 rue Paul Héroult

92000 Nanterre, France

Société Anonyme au capital de 98 337 521,70 euros

RCS Nanterre 542 010 053

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.mobil.fr/fr-fr/contact-us>

Tel. +33 (0)1 49 67 90 00

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product perfor

are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All procedures may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved