



## Mobil Super™ 2000 X1 10W-40

Mobil Passenger Vehicle Lube , Gabon

Premium Semi-Synthetic Passenger Vehicle Motor Oil

### Product Description

Mobil Super™ 2000 engine oils are premium engine oils and engineered to provide an excellent level of protection.

Mobil Super 2000 x1 10W-40 is formulated for city driving conditions of gasoline and diesel vehicles including passenger cars, light commercial vehicles and vans over a wide range of temperatures. Good wear protection and engine cleanliness helps to prolong engine life.

### Features and Benefits

Mobil Super 2000 x1 10W-40 provides:

- Effective sludge prevention
- Good engine cleanliness
- Robust wear protection
- High temperature protection

### Applications

Mobil Super 2000 products are formulated to give you confidence of protection beyond that of conventional oils. Mobil Super 2000 x1 10W-40 is recommended for:

- Older engine technologies
- Gasoline and Diesel without Diesel Particulate Filters (DPF)
- Passenger cars, SUV's, light commercial vehicles and vans
- Highway cruising and stop and go city driving
- Normal to occasionally severe operating conditions

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

### Specifications and Approvals

| <b>This product has the following approvals:</b> |
|--|
| VW 501 01  |
| VW 505 00  |
| AVTOVAZ (LADA cars)                              |
| MB-Approval 229.1                                |

| <b>This product is recommended for use in applications requiring:</b> |
|---|
| API CF  |

|   |
|---|
| <b>This product meets or exceeds the requirements of:</b> |
| API SL  |
| API SM  |
| API SN  |
| AAE (STO 003) Group B7                                    |
| API SJ  |
| API SN PLUS   |
| ACEA A3/B3  |

### Properties and Specifications

| Property   |            |
|--|------------|
| Grade  | SAE 10W-40 |
| Density @ 15 C, g/ml, ASTM D4052                           | 0.867      |
| Flash Point, Cleveland Open Cup, °C, ASTM D92              | 234        |
| Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445 | 14.2       |
| Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445  | 95         |
| Pour Point, °C, ASTM D97                                   | -33        |

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

06-2021

MOBIL OIL GABON

Zone Industrielle d'Oloumi, PO Box 145

Libreville

+ 241 74 23 01

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExxonMobil**



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved