



**Mobilube™ HD-A 85W-90**  
Mobil Commercial Vehicle Lube , United Kingdom  
Automotive Gear Lubricant

Product Description

Mobilube HD-A 85W-90 is a heavy duty gear lubricant formulated from high performance base oils and an advanced additive system. This lubricant is engineered for commercial transmissions, axles, and final drives where extreme pressures and shock loading are expected and is recommended by ExxonMobil for applications performance where API GL-5 service is required.

Features and Benefits

Today's heavy equipment applications place higher performance demands on drive-train lubricants. Higher speeds, higher torque, and heavier loads require improved formulations to maximise equipment life and minimise operating costs. Longer service intervals place additional demands on the gear lubricant requiring effective basestock and additive systems. Mobilube HD-A 85W-90 gear lubricant is engineered to meet these challenges. The key benefits include:

| Features  | Advantages and Potential Benefits   |
|---|---|
| Excellent thermal stability and resistance to high temperature oxidation  | Extended gear and bearing life due to minimal deposits<br>Longer seal life                |
| Good protection against low speed/high torque wear and against high speed scoring especially in heavily loaded rear axles | Increased load carrying capability<br>Reduced maintenance costs and longer equipment life |
| Effective rust and corrosion protection   | Reduced wear and longer component life  |
| Multipurpose capability   | Reduced number of gear lubricants required  |
| Compatible with typical automotive seals and gaskets  | Minimum leakage and reduced contamination   |
| Extended drain capability   | Increased productivity and reduced operating costs  |

Applications

Recommended by ExxonMobil for use in:

- Heavy duty automotive manual transmissions, axles, and final drives requiring API GL-5 level performance
- On highway cars and light trucks; heavy duty commercial vehicles
- Off highway industries including: construction, mining, quarrying, and agriculture
- Other gearboxes, steering gears and variable gearboxes
- Other heavy duty industrial and automotive applications involving hypoid gears operating under conditions where high speed/shock load, high speed/low torque, and/or low speed/high torque prevail

Specifications and Approvals

**This product has the following approvals:**

MB-Approval 235.0

ZF TE-ML 16C

ZF TE-ML 17B

ZF TE-ML 19B

ZF TE-ML 21A

**This product is recommended for use in applications requiring:**

MAN 342 Typ M1

**This product meets or exceeds the requirements of:**

API GL-5

ZF TE-ML 07A

## Properties and Specifications

| Property   |            |
|--|------------|
| Grade  | SAE 85W-90 |
| Density @ 15 C, kg/l, ASTM D4052                           | 0.9        |
| Flash Point, Cleveland Open Cup, °C, ASTM D92              | 222        |
| Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445 | 17         |
| Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445  | 184        |
| Pour Point, °C, ASTM D97                                   | -24        |
| Viscosity Index, ASTM D2270                                | 99         |

## Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

Esso Petroleum Company limited

ExxonMobil House, Ermyn Way, Leatherhead, Surrey KT22 8UX

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.mobil.co.uk/en-gb/contact-us-technical>

44 (0)1372 222000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

The ExxonMobil logo, featuring the word "Exxon" in a stylized font with a slanted 'x' and "Mobil" in a standard sans-serif font.

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved