



Mobilube HD-A Plus 80W-90

Mobil Commercial Vehicle Lube , United Kingdom

Automotive Gear Lubricant

Product Description

Mobilube HD-A Plus 80W-90 is engineered for commercial transmissions, axles, and final drives where extreme pressures and shock loading are expected and is recommended by ExxonMobil for applications where API GL-5 service is required. It is formulated from high performance base oils and an advanced additive system. This lubricant is a heavy duty gear lubricant allowing extended oil drain intervals predominantly in Mercedes Benz axles.

Features and Benefits

Today's heavy equipment applications place higher performance demands on drive-train lubricants. Higher speeds, higher torque, and heavier loads require improved formulations to maximise equipment life and minimise operating costs. Longer service intervals place additional demands on the gear lubricant requiring effective basestock and additive systems. Mobilube HD-A Plus 80W-90 gear lubricant is engineered to address these challenges. The key benefits include:

| Features | Advantages and Potential Benefits |
|---|--|
| Excellent thermal stability and resistance to high temperature oxidation | Long gear and bearing life due to minimal deposits. Long seal life. |
| Enhanced protection against low speed/high torque wear and against high speed scoring especially in heavily loaded rear axles | Increased load carrying capability Reduced maintenance costs and longer equipment life |
| Effective rust and corrosion protection | Reduced wear and longer component life |
| Multipurpose capability | Reduced number of gear lubricants required |
| Compatible with typical automotive seals and gaskets | Minimum leakage and reduced contamination |
| Extended drain capability | Increased productivity and reduced operating costs |

Applications

Recommended by ExxonMobil for use in:

- Heavy duty automotive manual transmissions, axles, and final drives requiring API GL-5 level performance
- On highway cars and light trucks; heavy duty commercial vehicles
- Off highway industries including: construction, mining, quarrying, and agriculture
- Other gearboxes, steering gears and variable gearboxes
- Other heavy duty industrial and automotive applications involving hypoid gears operating under conditions where high speed/shock load, high speed/low torque, and/or low speed/high torque prevail

Specifications and Approvals

| Mobilube HD-A Plus has the following builder approvals: | 80W-90 |
|---|--------|
| MB-Approval 235.20 | X |
| MAN 342 Typ M3 | X |
| MAN 341 Typ GA1 | X |
| ZF TE-ML 05A, 12L, 12M, 16B, 17B, 19B, 21A | X |

| Mobilube HD-A Plus meets or exceeds the requirements of the following industry and builder specifications: | |
|--|---|
| API GL-5 | X |
| SCANIA STO 1:0 | X |
| ZF TE-ML 07A | X |

Typical Properties

| Mobilube HD-A Plus 80W-90 | |
|----------------------------------|--------|
| SAE Grade | 80W-90 |
| Viscosity, ASTM D 445 | |
| cSt @ 40°C | 131 |
| cSt @ 100°C | 14.3 |
| Viscosity Index, ASTM D 2270 | 105 |
| Pour Point, °C, ASTM D 97 | -33 |
| Flash Point, °C, ASTM D 92 | 222 |
| Density @ 15°C kg/l, ASTM D 4052 | 0.901 |

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office or via the Internet, or will be provided by seller to customers if and as legally required. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design and Mobilube are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

09-2019

Esso Petroleum Company limited

ExxonMobil House, Ermyn Way, Leatherhead, Surrey KT22 8UX

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.mobil.co.uk/en-gb/contact-us-technical>

44 (0)1372 222000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved