



Mobil Paper Machine Oil S 220

Mobil Industrial , United Kingdom

Synthetic Paper Machine Oil

Product Description

MOBIL PAPER MACHINE OIL S 220 is a high performance synthetic lubricant specifically designed for demanding industrial paper machine circulating system engineered to provide exceptional lubrication characteristics not attainable with conventional premium mineral oil-based fluids. MOBIL PAPER MACHINE OIL S formulated to provide excellent protection of gears and bearings operating under severe conditions. It has a very low pour point and a naturally high viscosity index which helps ensure good low temperature start-up while maintaining excellent viscosity characteristics at very high temperatures. The low traction coefficient and viscosity index can help result in lower energy consumption and reduced component operating temperatures.

MOBIL PAPER MACHINE OIL S 220 is formulated with synthesized hydrocarbon fluid base oil technology and a proprietary additive system carefully balanced to high performance standards. This fluid permits the use of higher steam pressures, temperatures and machine speeds common in high output paper machine calendar rolls. The outstanding hydrolytic stability and filterability assure excellent performance in the presence of water and the ability to retain effective filtration at very fine filtration levels. It readily separates water and retains its colour characteristics for extended periods of operation under severe conditions.

Features and Benefits

The excellent performance capabilities of Mobil Paper Machine Oil S 220 in the area of wear protection, enhanced oxidation and chemical stability, effective rust corrosion protection, colour stability and filterability not only prolong maintenance service intervals but improve machine performance and increase production capacity. This can result in less required maintenance and longer equipment life.

| Features | Advantages and Potential Benefits |
|---|---|
| Excellent Wide Temperature Performance | Easier start-up and improved lubrication at cold startsVery good protection at elevated temperaturesBetter control of rates |
| Excellent Wear Protection | Improved bearing and gear performance |
| Outstanding Oxidation and Thermal Stability | Lower filter replacement costsCleaner systemsReduced system deposits |
| Effective Water Separation Properties | Allows easier removal of waterReduces formation of undesirable emulsions in systems |
| Excellent Filtration Properties | Helps to keep oil lines and flow control mechanisms free of depositsImproved oil flow and cooling performanceLowers replacement costs |
| Excellent Colour Stability | Ensuring flow meters can be easily monitored by eye so that the right flow rate is maintained to the bearings |
| High Level Rust and Corrosion Protection | Protects gears and bearings in wet environmentsProvides vapour space protection for areas of bearing and gear cavities and normally oil-wetted surfaces |

Applications

- Lubrication of severe industrial paper machine circulating systems
- Application involving circulation systems operating over a wide temperature range
- Circulation systems lubricating gears and bearings
- Mobil Paper Machine Oil S 220 is particularly applicable for machines where it is essential for excellent colour stability to visually monitor the oil flow rate through flow meters

Specifications and Approvals

| |
|---|
| |
| Voith Paper VS 108 5.3.6 2021-10 (winder) |
| Voith Paper VS 108 5.3.5 2021-10 (shoe press) |
| Voith Paper VS 108 5.3.2 2021-10 (dry end) |

Properties and Specifications

| Property | |
|--|------------|
| Grade | ISO VG 220 |
| Density @ 15.6 C, g/ml, ASTM D4052 | 0.865 |
| Emulsion, Time to 37 mL Water, 82 C, min, ASTM D1401 | 20 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 240 |
| FZG Scuffing, Fail Load Stage, A/8.3/90, ISO 14635-1 | 12 |
| Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445 | 27 |
| Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445 | 220 |
| Pour Point, °C, ASTM D97 | -39 |
| Viscosity Index, ASTM D2270 | 157 |
| Foam, Sequence I, Tendency, ml, ASTM D892 | 0 |
| Foam, Sequence I, Stability, ml, ASTM D892 | 0 |
| Foam, Sequence II, Tendency, ml, ASTM D892 | 0 |
| Foam, Sequence II, Stability, ml, ASTM D892 | 0 |
| Foam, Sequence III, Tendency, ml, ASTM D892 | 0 |
| Foam, Sequence III, Stability, ml, ASTM D892 | 0 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

The Mobil logotype and the Pegasus design are trademarks of ExxonMobil Corporation, or one of its subsidiaries

04-2024

Esso Petroleum Company limited

ExxonMobil House, Ermyn Way, Leatherhead, Surrey KT22 8UX

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.mobil.co.uk/en-gb/contact-us-technica>

44 (0)1372 222000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended

override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entit

ExxonMobil

Exxon

Mobil

Esso

XTOMobil

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved