



Mobil™ Gear Oil FE 75W

Mobil Passenger Vehicle Lube , United Kingdom

Manual Automotive Transmission Fluid

Product Description

Mobil Gear Oil FE 75W is a high performance gear oil blended from high quality mineral base oils and an advanced additive system to meet Peugeot's & Citroën specification. Mobil Gear Oil FE 75W is specially developed for PSA's (Peugeot / Citroën) manual gearboxes with integrated differentials. This product fully replaces Gear Oil BV 75W-80.

Features and Benefits

Mobil Gear Oil FE 75W is resistant to high temperature and protects from oxidation. Mobil Gear Oil FE 75W provides excellent cold flow and smooth gear shifting. Gear Oil FE 75W provides fuel economy benefits (*) over Mobil Gear Oil BV 75W-80 (PSA Factory Fill reference B71 2330) while maintaining the same du performance.

(*) fuel economy gain estimated by PSA Peugeot Citroën to 0.45% in MVEG cycle on MC, BE and ML transmissions) vs. Mobil Gear Oil BV 75W-80.

Applications

Mobil Gear Oil FE 75W is the only gear oil used for factory fill for all Peugeot & Citroën manual gearboxes fitted into PSA models in Europe. It is also fully bac compatible and suitable for use in all existing Peugeot and Citroën Manual Transmissions in Europe.

Specifications and Approvals

This product has the following approvals:

PSA B71 2310

Properties and Specifications

| Property | |
|------------------------------------------------------------|---------|
| Grade | SAE 75W |
| Density @ 15.6 C, g/cm ³ , ASTM D4052 | 0.882 |
| Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445 | 6.4 |
| Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445 | 35 |
| Pour Point, °C, ASTM D97 | -45 |
| Viscosity Index, ASTM D2270 | 134 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2022

Esso Petroleum Company limited

ExxonMobil House, Ermyn Way, Leatherhead, Surrey KT22 8UX

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.mobil.co.uk/en-gb/contact-us-technical>

44 (0)1372 222000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil

Esso

MTD

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved