



Mobil SHC™ Hydraulic EAL

Mobil Industrial , Greece

High Performance Synthetic Hydraulic Oil



Product Description

Mobil SHC™ Hydraulic EAL fluids are high performance biodegradable synthetic hydraulic oils for modern hydraulic systems. The fluids are designed to meet the demand for environmentally acceptable hydraulic lubricants. Mobil SHC Hydraulic EAL fluids are exceptionally high quality, wide-temperature, shear-stable hydraulic oils with controlled low-temperature pumpability properties and maximised anti-wear protection for hydraulic systems operating under high load and high pressures.

*Energy efficiency relates solely to the fluid performance when compared to ExxonMobil's standard hydraulic fluids. The technology used provides up to 3.6 % efficiency compared to Mobil DTE 25 when tested in a Eaton 25VMQ vane pump under controlled conditions in accordance with applicable industry standards and protocols. Efficiency improvements will vary based on operating conditions and application.

Features and Benefits

- Meets requirements for EU Ecolabel, Blue Angel, SS 155434 and USDA BioPreferred®.
- Outstanding load-carrying and anti-wear properties which protect system components against wear and scuffing and help provide long equipment life.
- Shear stable high viscosity index helps sustain component protection over a wide temperature range.
- Excellent thermal and oxidation stability that can help reduce maintenance downtime and costs by contributing to system cleanliness and deposit reduction, enabling long oil and filter life.
- Excellent demulsibility ensures ease of water removal in below waterline applications.
- Good elastomer compatibility; works well with same elastomers used with conventional mineral hydraulic oils.

Applications

- In systems where readily biodegradable and minimally toxic fluids may be required.
- Hydraulic applications where a reduction in energy consumption is desired.
- Circulation systems containing gears and bearings where mild extreme-pressure characteristics are desired.
- Systems containing servo-valves, where cleanliness is essential.
- Hydraulic systems operating with oil temperatures in the range of -17 °C (1.4° F) to +93 °C (199° F).
- Mobile, marine and forestry equipment operating in environmentally sensitive areas.
- Circulation systems operating under mild to moderate service conditions.
- Industrial hydraulic systems where leaked or spilled fluids could get into plant effluent.

Specifications and Approvals

This product has the following approvals:	32	46	68
--	-----------	-----------	-----------

This product has the following approvals:	32	46	68
Blue Angel RAL-UZ 178	X	X	X
Denison HF-1	X	X	X
Denison HF-2	X	X	X
Denison HF-6	X	X	X
Eaton Brochure No. 03-401-2010, Rev 1		X	X
HOCNF Norway-NEMS, Black	X	X	X
USDA Certified BioBased Product	X	X	X

This product meets or exceeds the requirements of:	32	46	68
AFNOR EU Ecolabel	X	X	X
ISO L-HEES (ISO 15380:2011)	X	X	X
JCMAS HKB VG32L	X		
JCMAS HKB VG46L		X	
Swedish Standard 15 54 34 AAV 32 Environmentally Acceptable (2015)	X		
Swedish Standard 15 54 34 AAV 46 Environmentally Acceptable (2015)		X	
Swedish Standard 15 54 34 AAV 68 Environmentally Acceptable (2015)			X
US EPA VGP:2013	X	X	X
WGK Non-Hazardous to water	X	X	X

Properties and Specifications

Property	32	46	68
Grade	ISO 32	ISO 46	ISO 68
Density @ 15 C, kg/l, ASTM D4052	0.936	0.930	0.923
FZG Scuffing, Fail Load Stage, A/8.3/90, ISO 14635-1	10	11	11
Flash Point, Cleveland Open Cup, °C, ASTM D92	282	298	292
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	6.2	7.7	11
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	31.1	43.3	71
Pour Point, °C, ASTM D97	-33	-42	-27
Viscosity Index, ASTM D2270	152	149	144

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

10-2020

ExxonMobil Lubricants & Specialties

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil Esso XTO ENERGY

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved