



## Mobil Delvac Legend™ 25W-50 High Mileage

Mobil Commercial Vehicle Lube , Guatemala

High Performance Diesel Engine Oil

### Product Description

Mobil Delvac Legend 25W-50 Alta Viscosidad, high performance diesel engine oil that provides proven protection for diesel engines operating in severe service applications. Mobil Delvac 25W-50 Alta Viscosidad is recommended for use in a wide range of heavy-duty applications and operating environments found in the trucking, mining, construction, quarrying, and agricultural industries.

### Features and Benefits

More than 90 year of experience and innovation supports the technology in Mobil Delvac Legend 25W-50 Alta Viscosidad. Delivers excellent performance in both naturally aspirated as well as turbo-charged diesel powered equipment. The key benefits include:

Features	Advantages and Potential Benefits
Thermal and oxidation stability	Controls sludge build-up and deposits
TBN reserve	Deposit control and acid neutralization
High Viscosity and Stay-in-grade shear stability	Reduced oil consumption, increased wear protection and high oil pressure across a wide operating temperature range
Excellent detergency/dispersancy	Cleaner engines and prolonged engine life
Component compatibility	Long gasket and seal life

### Applications

- Naturally aspirated and turbo-charged diesel powered equipment European, Japanese, and American manufacturers
- On-highway light and heavy-duty trucking
- Off-highway industries including: construction, mining, quarrying, and agriculture

### Specifications and Approvals

<b>This product is recommended for use in applications requiring:</b>
API CF-4

### Properties and Specifications

Property	
Grade	SAE 25W-50

Property	
Viscosity Index, ASTM D2270	116
Flash Point, Cleveland Open Cup, °C, ASTM D92	250
Density @ 15 C, g/ml, ASTM D1298	0.89
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	18.7
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	181.5
Pour Point, °C, ASTM D97	-27

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved