



Mobil Super™ 2000 5W-20

Mobil Passenger Vehicle Lube , Guyana

Premium Semi-Synthetic Passenger Vehicle Engine Oil

Product Description

Mobil Super™ 2000 5W-20 is an enhanced-premium semi-synthetic motor oil meeting the latest industry engine oil specifications. It is designed to provide an excellent level of protection and performance under the most demanding conditions

Features and Benefits

Mobil Super™ 2000 5W-20 is industry proven so you can trust you will get the performance you want from your vehicle. It contains low friction semi-synthetic formulation which increases engine efficiency and offers greater fuel economy. The American Petroleum Institute (API) classifies the 5W-20 viscosity grade as "Resource Conserving" engine lubricant and meets or exceeds ILSAC GF-5 / API SN Plus. Those claims are backward compatible with earlier performance levels such as API SN, SM, SL, and SJ and previous ILSAC categories.

Mobil Super™ 2000 5W-20 provides:

- Helps to promote long engine life.
- Its additive package provides excellent protection against engine wear and deposit formation.
- Provides superior engine protection during start up
- Excellent high temperature protection thanks to its high quality base oil formulation

Applications

Mobil Super™ 2000 5W-20 is formulated to give you confidence of protection beyond that of conventional oils. We particularly recommend it for the following vehicle types and conditions:

- Latest gasoline engine technologies
- Passenger cars, SUV's, light trucks and vans
- Stop and Go City Driving
- Normal to severe operating conditions
- Turbo-Chargers
- High Performance Engines

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product is recommended for use in applications requiring:

Ford WSS-M2C930-A

This product meets or exceeds the requirements of:

API SJ

API SL

This product meets or exceeds the requirements of:

API SM

API SN

API SN PLUS

API SN PLUS Resource Conserving

API SN Resource Conserving

API SP

API SP Resource Conserving

ILSAC GF-6A

Chrysler MS-6395

Ford WSS-M2C945-A

Ford WSS-M2C945-B1

Ford WSS-M2C960-A1

Properties and Specifications

| Property | |
|--|-----------|
| Grade | SAE 5W-20 |
| Viscosity Index, ASTM D2270 | 146 |
| Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445 | 8.3 |
| Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445 | 49 |
| Pour Point, °C, ASTM D97 | -42 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 226 |
| Density @ 15 C, g/ml, ASTM D4052 | 0.86 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

12-2021

Energy lives here™

ExxonMobil

Exxon Mobil ESSO XTO

© Copyright 2003-2022 Exxon Mobil Corporation. All Rights Reserved