



MOBIL ALTO KILOMETRAJE 25W60

Mobil Passenger Vehicle Lube , Honduras

High Mileage Conventional Engine Oil

Product Description

Mobil™ Alto Kilometraje is a unique formula that is especially designed for engines with over 100,000 kilometers. The 25W-60 viscosity provides a thick oil film that helps protect gasoline engines that operate in severe service such as high temperatures and in city traffic where stop-and-go driving is common. Mobil Alto Kilometraje is formulated from quality base stocks combined with performance additives, which help protect against the formation of sludge and corrosion.

Features and Benefits

Mobil Alto Kilometraje:

- Helps to reduce engine wear and corrosion in higher mileage vehicles
- Protects under a wide variety of operating conditions, especially high temperatures
- Helps reduce oil leakage due to the thick oil film
- Reduce oil consumption

Applications

Mobil Alto Kilometraje is recommended by ExxonMobil for higher mileage vehicles including turbo charged, super charged, fuel injected, multi-valve and normally aspirated engines. Before using Mobil Alto Kilometraje, consult the owner's manual of the vehicle for the manufacturer's recommended viscosity grade and API Service Classification.

Specifications and Approvals

This product meets or exceeds the requirements of:	
API SL	
API SJ	

Properties and Specifications

Property	
Grade	SAE 25W-60
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	24.5
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	262
Density @ 15 C, g/ml, ASTM D4052	0.899
Pour Point, °C, ASTM D97	-24
Flash Point, Cleveland Open Cup, °C, ASTM D92	270

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

ExxonMobil

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved