



## Mobil Delvac 1300 Series

Mobil Commercial Vehicle Lube , Haiti

High Performance Diesel Engine Oils

### Product Description

Mobil Delvac 1310, 1320, 1330, 1340, and 1350 are high performance monograde diesel engine oils formulated from advanced technology base oils and a balanced additive system. They are specifically engineered for performance in intercooled, turbo-charged engines operating under severe on and off-highway conditions. Mobil Delvac 1300 monogrades are used in a wide range of applications where a monograde lubricant is recommended.

### Features and Benefits

Features	Advantages and Potential Benefits
Excellent protection against oil thickening, high temperature deposits, sludge build-up, oil degradation and corrosion	Prolonged engine life Less wear Excellent protection against ring sticking
Extended TBN reserve	Long-term deposit/wear control Controls formation of acids when using higher sulfur fuels

### Applications

Recommended by ExxonMobil for use in:

- Naturally aspirated and turbo-charged diesel powered equipment
- On highway light and heavy duty trucking
- Off highway industries including: construction, mining, quarrying, and agriculture
- Hydraulic system and wet breaks in mobile equipment where a SAE 20 diesel engine oil is required (Delvac 1320)

### Specifications and Approvals

Mobil Delvac 1300 are also recommended by ExxonMobil for use in applications requiring:	MOBIL DELVAC 1320	MOBIL DELVAC 1330	MOBIL DELVAC 1340	MOBIL DELVAC 1350
API CF	X	X	X	X
API SF	X	X	X	X
MB 227.0	X			

### Properties and Specifications

Property	MOBIL DELVAC 1320	MOBIL DELVAC 1330	MOBIL DELVAC 1340	MOBIL DELVAC 1350

Property	MOBIL 1320	DELVAC	MOBIL 1330	DELVAC	MOBIL 1340	DELVAC	MOBIL 1350	DELVAC
Grade	SAE 20		SAE 30		SAE 40		SAE 50	
Ash, Sulfated, mass%, ASTM D874	1.1		1.1		1.1		1.1	
Density @ 15 C, g/ml, ASTM D4052	0.887		0.89		0.897		0.902	
Flash Point, Cleveland Open Cup, °C, ASTM D92	232		256		254		260	
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	8.4		11.8		14.6		19.9	
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	61		106		136		232	
Pour Point, °C, ASTM D97	-21		-21		-30		-18	
Total Base Number, mgKOH/g, ASTM D2896	10		10		10		10	
Viscosity Index, ASTM D2270	108		99		99		99	

### Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2020

Energy lives here™

**ExxonMobil**

Exxon Mobil  

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved